


## Certificate of UN test for Lithium ion battery

Customer Model : 42T4934  
 Global Code : F12272082  
 Product Name : 4UPF454261-2-LNV

  
 H. Kuroda General Manager  
 Technology Planning Department  
 Rechargeable Battery Business Division  
 SANYO Electric Co., Ltd.

We declare that this battery passed UN test.

Manual of Tests and Criteria (38.3 Lithium batteries)		Test results	Note	Number of test batteries/cells	
No.	Test item			First cycle	After 50 cycles
T 1	Altitude simulation	Pass		After 50 cycles fully charged 4 batteries	
T 2	Thermal test	Pass			
T 3	Vibration	Pass			
T 4	Shock	Pass			
T 5	External short circuit	Pass			
T 6	Impact	Pass		After 50 cycles fully discharged 5 cells	
T 7	Overcharge	Pass		After 50 cycles, Fully charged 4 batteries	
T 8	Forced discharge	Pass		After 50 cycles, fully discharged 10 cells	

\*The test data may contain additional test result other than above table.

### Lithium ion battery Specification

Item	Nominal value	Note
Watt-hour rating	43 Wh	
Nominal voltage	14.8 V	
Lithium equivalent content	3.42 g	

Above test procedures are compliant to the following manual.

(Manual of Tests and Criteria ST/AC.10/11, PartIII, sub-section 38.3, Rev.4 for cell, Rev.5A1 for battery)

# UN Test Data (Model: 4UPF454261-2-LNV)

1.Test Item: Altitude simulation (T1)

2.Test Purpose: This test simulates air transport under low-pressure conditions.

3.Test Procedure:

Test cells and batteries shall be stored at a pressure of 11.6kPa or less for at least six hours at ambient temperature(20±5°C).

SANYO Internal Procedure:

As above.

4.Test Requirements:

No mass loss(less than 0.1%),no leakage,no venting,no disassembly,no rupture and no fire,and the voltage retention is not less than 90%.

The requirement relating to voltage is not applicable to test batteries at fully discharged states.

5.Test Date: 2010/11/26

6.Test Data

Battery No.		Mass(g)		Mass loss (%) (=<0.1%)	Voltage(V)		Voltage Retention(%) (=>90%)	Other event	Result	Judgement
		Before test	After test		Before test	After test				
At first cycle,in fully charged states	1	252.40	252.44	0.02	16.56	16.55	99.9	0	PASS	PASS
	2	252.23	252.27	0.02	16.55	16.55	100.0	0	PASS	
	3	249.43	249.45	0.01	16.53	16.53	100.0	0	PASS	
	4	252.10	251.93	0.07	16.55	16.54	99.9	0	PASS	
At first cycle,in fully discharged states	5	249.72	249.77	0.02				0	PASS	
	6	252.04	252.09	0.02				0	PASS	
	7	249.17	249.21	0.02				0	PASS	
	8	250.02	250.05	0.01				0	PASS	
After 50 cycles ending in fully charged states	9	252.41	252.43	0.01	16.56	16.56	100.0	0	PASS	
	10	251.37	251.39	0.01	16.56	16.56	100.0	0	PASS	
	11	248.98	248.96	0.01	16.55	16.55	100.0	0	PASS	
	12	248.37	248.40	0.01	16.55	16.54	99.9	0	PASS	
After 50 cycles ending in fully discharged states	13	247.13	247.15	0.01				0	PASS	
	14	253.14	253.11	0.01				0	PASS	
	15	250.84	250.88	0.02				0	PASS	
	16	252.91	252.93	0.01				0	PASS	

Notes: L-Leakage, V-Venting, D-Disassembly, R-Rupture, F-Fire,  
0-No leakage, no venting, no disassembly, no rupture & no fire

## UN Test Data (Model: 4UPF454261-2-LNV)

1. Test Item: Thermal Test (T2)

2. Test Purpose: This test assesses cell and battery seal integrity and internal electrical connections. The test is conducted using rapid and extreme temperature changes.

3. Test Procedure:

Test cells and batteries are to be stored for at least six hours at a test temperature equal to  $75\pm 2^{\circ}\text{C}$ , followed by storage for at least six hours at a test temperature equal to  $-40\pm 2^{\circ}\text{C}$ . The maximum time interval between test temperature extremes is 30 minutes. This procedure is to be repeated 10 times, after which all test cells and batteries are to be stored for 24 hours at ambient temperature ( $20\pm 5^{\circ}\text{C}$ ). For large cells and batteries the duration of exposure to the test temperature extremes should be at least 12 hours.

SANYO Internal Procedure:

As above.

4. Test Requirements:

No mass loss (less than 0.1%), no leakage, no venting, no disassembly, no rupture and no fire, and the voltage retention is not less than 90%.

The requirement relating to voltage is not applicable to test batteries at fully discharged states.

5. Test Date: 2010/11/26-2010/12/2

6. Test Data

Battery No.	Mass(g)		Mass loss (%) (= $<0.1\%$ )	Voltage(V)		Voltage Retention(%) (= $\geq 90\%$ )	Other event	Result	Judgement	
	Before test	After test		Before test	After test					
At first cycle, in fully charged states	1	252.44	252.47	0.01	16.55	16.48	99.6	0	PASS	PASS
	2	252.27	252.31	0.02	16.55	16.49	99.6	0	PASS	
	3	249.45	249.46	0.00	16.53	16.49	99.8	0	PASS	
	4	251.93	251.99	0.02	16.54	16.48	99.6	0	PASS	
At first cycle, in fully discharged states	5	249.77	249.72	0.02				0	PASS	
	6	252.09	252.12	0.01				0	PASS	
	7	249.21	249.26	0.02				0	PASS	
	8	250.05	250.03	0.01				0	PASS	
After 50 cycles ending in fully charged states	9	252.43	252.46	0.01	16.56	16.49	99.6	0	PASS	
	10	251.39	251.41	0.01	16.56	16.48	99.5	0	PASS	
	11	248.96	248.99	0.01	16.55	16.47	99.5	0	PASS	
	12	248.40	248.42	0.01	16.54	16.48	99.6	0	PASS	
After 50 cycles ending in fully discharged states	13	247.15	247.17	0.01				0	PASS	
	14	253.11	253.16	0.02				0	PASS	
	15	250.88	250.89	0.00				0	PASS	
	16	252.93	252.96	0.01				0	PASS	

Notes: L-Leakage, V-Venting, D-Disassembly, R-Rupture, F-Fire,  
0-No leakage, no venting, no disassembly, no rupture & no fire

# UN Test Data (Model: 4UPF454261-2-LNV)

1. Test Item: Vibration (T3)

2. Test Purpose: This test simulates vibration during transport.

3. Test Procedure:

Cells and batteries are firmly secured to the platform of the vibration machine without distorting the cells in such a manner as to faithfully transmit the vibration. The vibration shall be a sinusoidal waveform with a logarithmic sweep between 7 Hz and 200 Hz and back to 7 Hz traversed in 15 minutes. This cycle shall be repeated 12 times for a total of 3 hours for each of three mutually perpendicular mounting positions of the cell. One of the directions of vibration must be perpendicular to the terminal face.

The logarithmic frequency sweep is as follows: from 7 Hz a peak acceleration of 1gn is maintained until 18 Hz is reached. The amplitude is then maintained at 0.8 mm (1.6 mm total excursion) and the frequency increased until a peak acceleration of 8gn occurs (approximately 50Hz). A peak acceleration of 8 gn is then maintained until the frequency is increased to 200Hz.

SANYO Internal Procedure:

As above.

4. Test Requirements:

No mass loss (less than 0.1%), no leakage, no venting, no disassembly, no rupture and no fire, and the voltage retention is not less than 90%.

The requirement relating to voltage is not applicable to test batteries at fully discharged states.

5. Test Date: 2010/12/3-2010/12/6

6. Test Data

Battery No.	Mass(g)		Mass loss (%) (= < 0.1%)	Voltage(V)		Voltage Retention(%) (= > 90%)	Other event	Result	Judgement	
	Before test	After test		Before test	After test					
At first cycle, in fully charged states	1	252.47	252.46	0.00	16.48	16.45	99.8	0	PASS	PASS
	2	252.31	252.33	0.01	16.49	16.46	99.8	0	PASS	
	3	249.46	249.48	0.01	16.49	16.44	99.7	0	PASS	
	4	251.99	251.98	0.00	16.48	16.46	99.9	0	PASS	
At first cycle, in fully discharged states	5	249.72	249.76	0.02				0	PASS	
	6	252.12	252.13	0.00				0	PASS	
	7	249.26	249.28	0.01				0	PASS	
	8	250.03	250.06	0.01				0	PASS	
After 50 cycles ending in fully charged states	9	252.46	252.44	0.01	16.49	16.45	99.8	0	PASS	
	10	251.41	251.42	0.00	16.48	16.44	99.8	0	PASS	
	11	248.99	248.96	0.01	16.47	16.45	99.9	0	PASS	
	12	248.42	248.48	0.02	16.48	16.47	99.9	0	PASS	
After 50 cycles ending in fully discharged states	13	247.17	247.19	0.01				0	PASS	
	14	253.16	253.17	0.00				0	PASS	
	15	250.89	250.88	0.00				0	PASS	
	16	252.96	252.99	0.01				0	PASS	

Notes: L-Leakage, V-Venting, D-Disassembly, R-Rupture, F-Fire,  
 0-No leakage, no venting, no disassembly, no rupture & no fire

# UN Test Data (Model: 4UPF454261-2-LNV)

1. Test Item: Shock (T4)

2. Test Purpose: This test simulates possible impacts during transport.

3. Test Procedure:

Test cells and batteries shall be secured to the testing machine by means of a rigid mount which will support all mounting surfaces of each test battery. Each cell or battery shall be subjected to a half-sine shock of peak acceleration of 150 g<sub>n</sub> and pulse duration of 6 milliseconds. Each cell or battery shall be subjected to three shocks in the positive direction followed by three shocks in the negative direction of three mutually perpendicular mounting positions of the cell or battery for a total of 18 shocks.

However, large cells and large batteries shall be subjected to a half-sine shock of peak acceleration of 50 g<sub>n</sub> and pulse duration of 11 milliseconds. Each cell or battery is subjected to three shocks in the positive direction followed by three shocks in the negative direction of each of three mutually perpendicular mounting positions of the cell for a total of 18 shocks.

SANYO Internal Procedure:

As above.

4. Test Requirements:

No mass loss (less than 0.1%), no leakage, no venting, no disassembly, no rupture and no fire, and the voltage retention is not less than 90%.

The requirement relating to voltage is not applicable to test batteries at fully discharged states.

5. Test Date: 2010/12/6

6. Test Data

Battery No.	Mass(g)		Mass loss (%) (= < 0.1%)	Voltage(V)		Voltage Retention(%) (= > 90%)	Other event	Result	Judgement	
	Before test	After test		Before test	After test					
At first cycle, in fully charged states	1	252.460	252.480	0.01	16.45	16.45	100.0	0	PASS	PASS
	2	252.330	252.370	0.02	16.46	16.46	100.0	0	PASS	
	3	249.480	249.440	0.02	16.44	16.44	100.0	0	PASS	
	4	251.980	251.960	0.01	16.46	16.46	100.0	0	PASS	
At first cycle, in fully discharged states	5	249.760	249.790	0.01				0	PASS	
	6	252.130	252.150	0.01				0	PASS	
	7	249.280	249.310	0.01				0	PASS	
	8	250.060	250.050	0.00				0	PASS	
After 50 cycles ending in fully charged states	9	252.440	252.490	0.02	16.45	16.45	100.0	0	PASS	
	10	251.420	251.460	0.02	16.44	16.44	100.0	0	PASS	
	11	248.960	248.980	0.01	16.45	16.44	99.9	0	PASS	
	12	248.480	248.450	0.01	16.47	16.46	99.9	0	PASS	
After 50 cycles ending in fully discharged states	13	247.190	247.220	0.01				0	PASS	
	14	253.170	253.180	0.00				0	PASS	
	15	250.880	250.900	0.01				0	PASS	
	16	252.990	252.940	0.02				0	PASS	

Notes: L-Leakage, V-Venting, D-Disassembly, R-Rupture, F-Fire,  
0-No leakage, no venting, no disassembly, no rupture & no fire

## UN Test Data (Model: 4UPF454261-2-LNV )

1.Test Item: External short circuit (T5)

2.Test Purpose: This test simulates an external short circuit.

3.Test Procedure:

The cell or battery to be tested shall be temperature stabilized so that its external case temperature reaches  $55\pm 2^{\circ}\text{C}$  and then the cell or battery shall be subjected to a short circuit condition with a total external resistance of less than 0.1ohm at  $55\pm 2^{\circ}\text{C}$ .This short circuit condition is continued for at least one hour after the cell or battery external case temperature has returned to  $55\pm 2^{\circ}\text{C}$ . The cell or battery must be observed for a further six hours for the test to be concluded.

SANYO Internal Procedure:

As above.

4.Test Requirements:

External temperature of test batteries does not exceed  $170^{\circ}\text{C}$  and there is no disassembly,no rupture and no fire within six hours of this test.

5.Test Date: 2010/12/ 6-12/7

6.Test Data

Battery No.	Maximum temperature ( $^{\circ}\text{C}$ )	Other event	Result	Judgement
At first cycle,in fully charged states	1	54.6	0	PASS
	2	54.7	0	PASS
	3	54.7	0	PASS
	4	54.7	0	PASS
At first cycle,in fully discharged states	5	54.6	0	PASS
	6	54.5	0	PASS
	7	54.7	0	PASS
	8	55.0	0	PASS
After 50 cycles ending in fully charged states	9	55.1	0	PASS
	10	55.1	0	PASS
	11	54.3	0	PASS
	12	54.5	0	PASS
After 50 cycles ending in fully discharged states	13	55.0	0	PASS
	14	55.2	0	PASS
	15	54.8	0	PASS
	16	54.5	0	PASS

PASS

Notes: D-Disassembly, R-Rupture, F-Fire, 0-No disassembly, no rupture & no fire

## UN Test Data (Model: 4UPF454261-2-LNV)

1. Test Item: Impact (T6)

2. Test Purpose: This test simulates an impact.

3. Test Procedure:

The test sample cell or component cell is to be placed on a flat surface. A 15.8mm diameter bar is to be placed across the centre of the sample. A 9.1kg mass is to be dropped from a height of  $61 \pm 2.5$ cm onto the sample.

A cylindrical or prismatic cell is to be impacted with its longitudinal axis parallel to the flat surface and perpendicular to the longitudinal axis of the 15.8mm diameter curved surface lying across the centre of the test sample. A prismatic cell is also to be rotated 90 degrees around its longitudinal axis so that both the wide and narrow sides will be subjected to the impact. Each sample is to be subjected to only a single impact. Separate samples are to be used for each impact.

A coin or button cell is to be impacted with the flat surface of the sample parallel to the flat surface and the 15.8mm diameter curved surface lying across its centre.

SANYO Internal Procedure:

As above.

4. Test Requirements:

External temperature of test batteries does not exceed  $170^{\circ}\text{C}$  and there is no disassembly and no fire within six hours of this test.

5. Test Date: 2007/08/08

6. Test Data

Cell No.	Maximum Temperature( $^{\circ}\text{C}$ )	Other event	Result	Judgement
At first cycle, 50% charged states	1	45.0	0	PASS
	2	88.3	0	PASS
	3	38.2	0	PASS
	4	89.0	0	PASS
	5	35.6	0	PASS
	6	86.2	0	PASS
	7	85.4	0	PASS
	8	58.5	0	PASS
	9	88.6	0	PASS
	10	81.9	0	PASS
After 50 cycles ending, in fully discharged states	11	33.1	0	PASS
	12	34.3	0	PASS
	13	36.4	0	PASS
	14	44.3	0	PASS
	15	40.4	0	PASS
	16	40.8	0	PASS
	17	43.0	0	PASS
	18	39.8	0	PASS
	19	44.2	0	PASS
	20	42.9	0	PASS

Notes: D-Disassembly, F-Fire, 0-No disassembly & no fire

## UN Test Data (Model: 4UPF454261-2-LNV )

1.Test Item:Overcharged (T7)

2.Test Purpose: This test evaluates the ability of a rechargeable battery to withstand an overcharge condition.

3.Test Procedure:

The charge current shall be twice the manufacturer's recommended maximum continuous charge current.

The minimum voltage of the test shall be as follows:

(a) when the manufacturer's recommended charge voltage is not more than 18V, the minimum voltage of the test shall be the lesser of two times the maximum charge voltage of the battery or 22V.

(b) when the manufacturer's recommended charge voltage is more than 18V, the minimum voltage of the test shall be 1.2 times the maximum charge voltage.

Tests are to be conducted at ambient temperature. The duration of the test shall be 24 hours.

SANYO Internal Procedure:

Min.Charge Voltage:	22 V
Charge Current:	4.06 A

4.Test Requirements:

There is no disassembly and no fire within seven days of the test.

5.Test Date: 2010/11/26-2010/12/3

6.Test Data

Battery No.	Event	Result	Judgement
At first cycle in fully charged states	1	0	PASS
	2	0	PASS
	3	0	PASS
	4	0	PASS
After 50 cycles ending in fully charged states	5	0	PASS
	6	0	PASS
	7	0	PASS
	8	0	PASS
			PASS

Notes: D-Disassembly, F-Fire, 0-No disassembly & no fire



## UN Test Data (Model: 4UPF454261-2-LNV)

1. Test Item: Forced discharge (T8)

2. Test Purpose: This test evaluates the ability of a primary or a rechargeable cell to withstand a forced discharged condition.

3. Test Procedure:

Each cell shall be forced discharged at ambient temperature by connecting it in series with a 12V D.C. power supply at an initial current equal to the maximum discharge current specified by the manufacturer. The specified discharge current is to be obtained by connecting a resistive load of the appropriate size and rating in series with the test cell. Each cell shall be forced discharged for a time interval (in hours) equal to its rated capacity divided by the initial test current (in Ampere).

SANYO Internal Procedure:

As above.

4. Test Requirements:

There is no disassembly and no fire within seven days of the test.

5. Test Date: 2007/08/09

6. Test Data:

Cell No.	Event	Result	Judgement
At first cycle, in fully discharged states	1	0	PASS
	2	0	PASS
	3	0	PASS
	4	0	PASS
	5	0	PASS
	6	0	PASS
	7	0	PASS
	8	0	PASS
	9	0	PASS
	10	0	PASS
After 50 cycles ending, in fully discharged states	11	0	PASS
	12	0	PASS
	13	0	PASS
	14	0	PASS
	15	0	PASS
	16	0	PASS
	17	0	PASS
	18	0	PASS
	19	0	PASS
	20	0	PASS

Notes: D-Disassembly, R-Rupture, F-Fire, 0-No disassembly, no rupture & no fire