

LG Chem, Ltd.  
128, Yeoui-daero, Yeongdeungpo-gu, Seoul, Korea  
Global Standard Certification Part  
Tel: 82-42-870-6195, Fax: 82-42-863-0182

If any of pages is not legible or has not been received, please notify our office for re-transmission

## CERTIFICATE OF COMPLIANCE

The following product has been evaluated according to the 6<sup>th</sup> revised edition of the UN Manual of Tests and Criteria.

We, LG Chem, Ltd., hereby certify that this battery meets the requirements of the regulation for transportation of lithium-ion cells, batteries and single cell batteries.


<input type="checkbox"/> Lithium-ion cell <input checked="" type="checkbox"/> Lithium-ion battery <input type="checkbox"/> Lithium-ion single cell battery	
Model name	<b>L17L3PE0</b>
Cell Model name	<b>ICP595490A1</b>
Nominal voltage	<b>11.4 V</b>
Electric power capacity	<b>51.50 Wh</b>

Reviewed By: MinJe Woo

Approved By: DaeHo Nam



Assistant Manager  
Global Standard Certification Part  
LG Chem, Ltd.  
E-mail: [milkis@lgchem.com](mailto:milkis@lgchem.com)



Senior Manager  
Global Standard Certification Part  
LG Chem, Ltd.  
E-mail: [kkammy@lgchem.com](mailto:kkammy@lgchem.com)

Document Number	QDI-170911-B-L17L3PE0	
Prepared	MyeongHoon Choi	<i>Choi</i>
Reviewed	MinJe Woo	<i>[Signature]</i>
Approved	DaeHo Nam	<i>[Signature]</i>

# UN38.3 Test Report

## - L17L3PE0 (Nom.51.5Wh, 11.4V) -

### Index

1. UN38.3 Test Condition
2. General Information
3. Test Result
4. Sample Image

2017. 09. 11

# 1. UN38.3 Test Condition

Test item	Test Condition	Requirements	Etc.
Test 1. Altitude Simulation	Storing at (low pressure) 11.6kPa for 6hr at 20+/-5℃		T1~T5 : Sequence Tests <pre> graph TD     T1[Test 1 Altitude Simulation] --&gt; T2[Test 2 Thermal Test]     T2 --&gt; T3[Test 3 Vibration]     T3 --&gt; T4[Test 4 Shock]     T4 --&gt; T5[Test 5 Ext. Short Circuit]           </pre>
Test 2. Thermal Test	[72±2℃, 6hr ↔ -40±2℃, 6hr, interval max. 30min] x 10cycle Storing at 20±5℃ for 24h		
Test 3. Vibration	[7Hz↔200Hz↔7Hz, in 15min] x 12 times x 3 direction 1) sinusoidal waveform with a logarithmic sweep 2) 7Hz 18Hz (maintaining 1gn) app. 50Hz (until 8gn) 200Hz (maintaining 8gn), 1.6mm total excursion	<ul style="list-style-type: none"> <li>- After OCV (%) ≥ 90%</li> <li>- No leakage, no venting, no disassembly, no rupture, no fire</li> <li>- Mass loss limit (leakage)               <ol style="list-style-type: none"> <li>1) If M&lt;1g, less than 0.5%,</li> <li>2) If 1g≤M≤75g, less than 0.2%,</li> <li>3) If M&gt;75g, less than 0.1%</li> </ol> </li> </ul>	
Test 4. Shock	Half sine shock 1) Peak acceleration - For cells & single cell batteries : 150gn - For batteries (whichever is smaller) : 150gn or $\sqrt{\frac{100850}{\text{Mass}(kg)}} \text{ gn}$ 2) Pulse duration : 6msec 3) 6 direction (±x, y, z) x 3 cycle		
Test 5. External Short Circuit	1) Samples to be heated to 57±4℃ in chamber (Measured on external case) 2) Less than 0.1Ω, ext. short-circuit at 57±4℃ 3) 1hr continue after returning to 57±4℃	<ul style="list-style-type: none"> <li>- No disassembly, no rupture, no fire within 6 hours after the test</li> <li>- Max. Temp ≤ 170℃</li> </ul>	
Test 6. Impact	Φ=15.8±0.1mm bar, 9.1±0.1kg mass, 61±2.5cm height	<ul style="list-style-type: none"> <li>- No disassembly, no fire within 6 hours after the test</li> <li>- Max. Temp ≤ 170℃</li> </ul>	for cylindrical cells (not less than 18mm diameter)
Test 6. Crush	Crushing rate : 1.5cm/s, until 13kN±0.78kN or 100mV drop or 50% deformation		for cylindrical cells (less than 18mm diameter) for prismatic, pouch, coin/button cells
Test 7. Overcharge	Current = Manufacturer's recommended max. continuous charge current X 2 Voltage 1.If charge voltage ≤ 18V, V (min.) = 2 x (max. charge voltage) or 22V. 2.If charge voltage > 18V, V (min.) = 1.2 x (max. charge voltage)	<ul style="list-style-type: none"> <li>- No disassembly, no fire within 7 days after the test</li> </ul>	Only for Single Cell Battery / Battery
Test 8. Forced Discharge	Discharge at max. discharge current (connecting in series with 12V DC power supply), Duration time = rated capacity/initial test current	<ul style="list-style-type: none"> <li>- No disassembly, no fire within 7 days after the test</li> </ul>	Resistance of Electric Loader 1/Ω = (max. discharge current) / (12 + Initial OCV)

## 2. General Information

### 1. Standard charge / discharge Condition

	Mode	Condition	End Condition
Charge	CC / CV	Current = 4390 mA Voltage = 13.05 V	Current = 225 mA
Discharge	CC	Current = 900 mA	Voltage = 9.6 V

### 2. Cycle Condition

	Mode	Condition	End Condition
Charge	CC / CV	Current = 4390 mA Voltage = 13.05 V	Current = 225 mA
Discharge	CC	Current = 900 mA	Voltage = 9.6 V

### 3. Test Condition

	Mode	Condition
Test 7. Overcharge	CC / CV	Max. Charge Current = 5700 mA CC/CV 2Imax (11400mA) 22 V cut-off 24Hr
Test 8. Forced Discharge	CC	Max. Discharge Current = 9000 mA Duration Time = 30 min

# 3-1. T1-T4 Test Result

Before			Altitude (T1)					Thermal (T2)					Vibration (T3)					Shock (T4)				
Pack NO.	OCV	Mass (g)	After OCV (V)	Mass (g)	After OCV(%)	Mass Loss(%)	Result	After OCV (V)	Mass (g)	After OCV(%)	Mass Loss(%)	Result	After OCV (V)	Mass (g)	After OCV(%)	Mass Loss(%)	Result	After OCV (V)	Mass (g)	After OCV(%)	Mass Loss(%)	Result

## A. 1st cycle fully charged state

1	13.027	239.13	13.016	239.12	99.92	0.004	Pass	12.811	239.11	98.43	0.004	Pass	12.806	239.10	99.96	0.004	Pass	12.805	239.10	99.99	0.000	Pass
2	13.048	239.12	13.045	239.11	99.98	0.004	Pass	12.844	239.10	98.46	0.004	Pass	12.837	239.09	99.95	0.004	Pass	12.836	239.07	99.99	0.008	Pass
3	13.043	239.12	13.042	239.11	99.99	0.004	Pass	12.837	239.10	98.43	0.004	Pass	12.828	239.08	99.93	0.008	Pass	12.825	239.06	99.98	0.008	Pass
4	13.013	239.11	13.011	239.10	99.98	0.004	Pass	12.809	239.09	98.45	0.004	Pass	12.805	239.08	99.97	0.004	Pass	12.801	239.07	99.97	0.004	Pass

## B. 50th cycle fully charged state

5	13.054	238.97	13.045	238.97	99.93	0.000	Pass	12.842	238.96	98.44	0.004	Pass	12.839	238.95	99.98	0.004	Pass	12.829	238.95	99.92	0.000	Pass
6	13.029	238.92	13.019	238.92	99.92	0.000	Pass	12.817	238.91	98.45	0.004	Pass	12.811	238.91	99.95	0.000	Pass	12.809	238.90	99.98	0.004	Pass
7	13.027	238.90	13.025	238.88	99.98	0.008	Pass	12.823	238.87	98.45	0.004	Pass	12.814	238.87	99.93	0.000	Pass	12.806	238.86	99.94	0.004	Pass
8	13.031	238.87	13.026	238.87	99.96	0.000	Pass	12.822	238.86	98.43	0.004	Pass	12.818	238.85	99.97	0.004	Pass	12.808	238.85	99.92	0.000	Pass

# 3-2. T5/T7 Test Result

## EXT.Short Circuit (T5)

Pack NO.	Initial OCV(V)	Max. Temp (°C)	Result
----------	----------------	----------------	--------

### A. 1st cycle fully charged state

1	12.805	56.32	Pass
2	12.836	55.09	Pass
3	12.825	55.57	Pass
4	12.801	55.32	Pass

### B. 50th cycle fully charged state

5	12.829	56.29	Pass
6	12.809	54.74	Pass
7	12.806	55.45	Pass
8	12.808	56.27	Pass

## Over Charge (T7)

Pack NO.	Initial OCV(V)	Max. Temp (°C)	Result
----------	----------------	----------------	--------

### A. 1st cycle fully charged state

9	13.047	24.13	Pass
10	13.043	24.88	Pass
11	13.047	25.00	Pass
12	13.035	24.07	Pass

## Over Charge (T7)

Pack NO.	Initial OCV(V)	Max. Temp (°C)	Result
----------	----------------	----------------	--------

### B. 50th cycle fully charged state

13	13.027	24.01	Pass
14	13.029	24.66	Pass
15	13.029	24.89	Pass
16	13.028	24.35	Pass

# 3-3. T6/T8 Test Result (ICP595490A1)

## Crush (T6)

NO.	Initial OCV(V)	Max. Temp (°C)	Result
-----	----------------	----------------	--------

### A. 1st cycle 50% charged state

C-1	3.822	20.45	Pass
C-2	3.823	20.52	Pass
C-3	3.823	21.43	Pass
C-4	3.824	20.80	Pass
C-5	3.824	22.09	Pass

## Forced Discharge (T8)

NO.	Initial OCV(V)	Max. Temp (°C)	Result	NO.	Initial OCV(V)	Max. Temp (°C)	Result
-----	----------------	----------------	--------	-----	----------------	----------------	--------

### A. 1st cycle fully discharged state

C-6	3.221	103.92	Pass	C-16	3.314	85.24	Pass
C-7	3.218	116.05	Pass	C-17	3.309	98.81	Pass
C-8	3.230	105.14	Pass	C-18	3.320	106.37	Pass
C-9	3.219	98.71	Pass	C-19	3.331	103.76	Pass
C-10	3.231	113.00	Pass	C-20	3.316	73.64	Pass
C-11	3.221	94.48	Pass	C-21	3.318	105.77	Pass
C-12	3.212	103.91	Pass	C-22	3.312	103.81	Pass
C-13	3.208	105.73	Pass	C-23	3.313	87.25	Pass
C-14	3.248	97.84	Pass	C-24	3.316	89.89	Pass
C-15	3.256	99.20	Pass	C-25	3.313	94.44	Pass

### B. 50th cycle fully discharged state

# 4. Sample Image

