

Jan. 09. 2009

**Certificate of UN test for Lithium ion battery**

Customer Model : 92P1183  
 Sanyo Model : 3UR18650F-2-CPL-10  
 Sanyo Product Code : F164A0191

SANYO Electric Co., Ltd.  
 Mobile Energy Company  
 Battery System Development  
 Management Department  
  
 M. Kanbayashi Senior Manager  
 Technical Administration Department

Manual of Tests and Criteria (38.3 Lithium batteries)		Test results	Note	Number of test batteries		
No.	Test item			First cycle	First cycle fully Discharged	After 50 cycles
T 1	Altitude simulation	Pass			After 50 cycles	
T 2	Thermal test	Pass			fully discharged	
T 3	Vibration	Pass			4 batteries	
T 4	Shock	Pass			4 batteries	
T 5	External short circuit	Pass			4 batteries	
T 6	Impact	Pass		First cycle 50% charged 5 cells for cylindrical cell, 10 cells for prismatic cell, 5 cells for coin cell.	After 50 cycles, fully discharged 5 cells for cylindrical cell, 10 cells for prismatic cell, 5 cells for coin cell.	
T 7	Overcharge	Pass	For battery only	First cycle fully charged 4 batteries	After 50 cycles, fully charged 4 batteries	
T 8	Forced discharge	—	For cell only	For cell only		

**Lithium ion battery Specification**

Item	Nominal value	Note
Watt-hour rating	48 Wh	

We declare the above : The test result mentioned above was checked according to UN test.  
 (Manual of Tests and Criteria ST/SG/AC.10/11/Rev.4, PartIII, sub-section 38.3)