



ECMA/TC38-TG3/2015/026 (Rev. 1 – 15 April 2015)

## Annex B2 - Product environmental attributes Notebooks and Tablets

The declaration may be published only when all rows and/or fields marked with \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Lenovo	Logo			
Company name *	Lenovo	1 . <u> </u>			
Contact information *	Lenovo Global Environmental Affairs	0001/0			
e-mail address	Alvin L Carter	Lenovo			
	<u>alcarter@lenovo.com</u>				
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment	.html			
Additional information	The latest version of this document can be found at:				
	http://www.lenovo.com/ecodeclaration				

The company declares (based on product specification or test results based obtained from sample testing), that the product						
conforms to the statemen	conforms to the statements given in this declaration.					
Type of product *	Notebook					
Commercial name *	IdeaPad Flex 5 Chrome 13ITL6					
Model number *	82M7					
Issue date *	2021-4-27					
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other					
Additional information						

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

#### About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template:

P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products

Model number *		82M7	Logo	Long	N/6	
Issue date *		2021-4-27		Lend	JVC	<b>)</b> <sub>m.</sub>
Product	environ	mental attributes - Legal requirements		Require	ment	met
Item				Yes	No	n.a.
P1		ous substances and preparations				
P1.1*	Products	do comply with current European RoHS Directive. (See legal reference and NOTE	EB1)	$\boxtimes$		
P1.2*		do not contain Asbestos (see legal reference). ht: Legal reference has no maximum concentration value.				
P1.3*	Products hydrobro trichloroe	do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), smofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachethane, methyl bromide (see legal reference). Comment: Legal reference has no mation values.				
P1.4*		do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychel (PCT) in preparations (see legal reference).	lorinated			
P1.5*	Products	do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 car ntaining at least 48% per mass of chlorine in the SCCP (see legal reference).	bon atoms in t	ne 🔀		
P1.6*	(see lega	h direct and prolonged skin contact do not release nickel in concentrations above ( al reference). nt: Max limit in legal reference when tested according to EN1811:2011-5.	),5 μg/cm²/wee	ek 🔀		
P1.7*	REACH	Article 33 information about substances in articles is available at (add URL or mail <a href="https://www.lenovo.com/us/en/Lenovo-REACH-SVHC-Disclosure">www.lenovo.com/us/en/Lenovo-REACH-SVHC-Disclosure</a>	contact):	$\boxtimes$		
P2	Batterie					
P2.1*		duct contains a battery or an accumulator, the battery/accumulator is labeled with Information on proper disposal is provided in user manual. (See legal reference)	the disposal			
P2.2*	Batteries	s or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadne)	nium. (See leg	al 🔀		
P2.3*	Batteries	and accumulators are readily removable. (See legal reference)		$\boxtimes$		
P3	Conforn	nity verification & Eco design (ErP)				
P3.1*	The D	duct is CE-marked to show conformance with applicable legal requirements (see legelaration of Conformity can be requested at (add link or e- tyww.lenovo.com/us/en/compliance/eu-doc	gal reference). ·mail addres			
P3.2*		duct complies with the Eco design requirements for energy-related products, al reference).				
	Required	d information is; given in item P15 or added to this document,  available at (add URL):				
DE		www.lenovo.com/us/en/compliance/eco-declaration packaging				
P5.1*		ng and packaging components do not contain more than 0,01% lead, mercur	v cadmium a	nd 🔀		
	hexavale	ent chromium by weight of these together.				
P5.2*	used (se	kaging materials are marked with abbreviations and numbers indicating the nature e legal reference).				
P5.3*	(see lega	luct packaging material is free from ozone depleting substances as specified in the N al reference). nt: Legal reference has no maximum concentration values.	Montreal Proto	col 🔀		
P6		nt information				
P6.1*		on for recyclers/treatment facilities is available (see legal reference).		$\boxtimes$		

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model number *		82M7 Logo	Lon	01/6	
Issue da	ite *	2021-4-27	Len	OVC	) <sub>TM</sub>
Produc	t environ	mental attributes - Market requirements (See General NOTE GN below)			
		onmental conscious design	Require	ment	met
Item		tory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a.
P7		Disassembly, recycling at have to be treated separately are easily separable		_	
P7.1*					井
P7.2*		naterials in covers/housing have no surface coating.			Щ.
P7.3*		arts > 100 g consist of one material or of easily separable materials.		<u>Ц</u>	Щ.
P7.4*		arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.		Ц_	Щ.
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.				_ <u>_</u> _
P7.6*		re easily separable. (This requirement does not apply to safety/regulatory labels).	$\boxtimes$		
D7.7*		lifetime		_	
P7.7*		ng can be done e.g. with processor, memory, cards or drives		<u> </u>	<u> </u>
P7.8*		ng can be done using commonly available tools	$\square$		Щ.
P7.9		arts are available after end of production for: 5 years			Щ.
P7.10		s available after end of production for: 5 years			
D7 44*		and substance requirements			
P7.11*		cover/housing material type (e.g. plastics, metal, aluminum): type: PC+ABS  Material type:			
P7.12		n materials of external electrical cables are PVC free.		$\square$	
P7.13		n materials of internal electrical cables are PVC free.	-H	$\square$	∺
P7.14		plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1%	% 🔀		∺
1 7.14		1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, an		Ш	Ш
		chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing	g		
D7.45		an 25% post-consumer recycled content.			
P7.15	as define	circuit boards, PCBs (without components) are low halogen: all	n 📙		<u> </u>
P7.16	Marking:				
P7.17		nemical specifications of flame retardants in printed circuit boards > 25 g (without components):			
		PA (additive), TBBPA (reactive) (See NOTE B3), Other: DOPO, CAS #: 35948-25-5		Ш	Ш
		nemical specifications of flame retardants in printed circuit boards (without components) > 25 g g ISO 1043-4:			
	accordin	g 13O 1043-4.		ш	ш
P7.18	Alt. 1		-		
		etarded plastic parts >25g contain the following flame retardant substances/preparations is rations above 0.1%:	in 🔀		
		ent: No legal limits exist, this is a market requirement.			
		ical name: halogen-free organic phosphorus compound CAS #: confidential			
		ical name: CAS #:			
		ical name: CAS #: ical name: CAS #:			
	Alt. 2	ournance. Grown			
		al specifications of flame retardants in plastic parts >25g according ISO 1043-4:			
P7.19		parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been and Hazard statements:			
		rce(s) for these classifications is/are found at (add URL(s)): , (See note B5)			
P7.20*	Postcons	sumer recycled plastic material content is used in the product (See Note B6):	$\boxtimes$		
	a) Of t a po or	at least one of the two alternatives below shall be answered; total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as ercentage of total plastic by weight) is 3.5%.			
	b) The	e weight of recycled material is 13.5 g.			

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model number *	82M7	Logo	Lenovo			
Issue date *	2021-4-27			Len		) <sub>TH</sub>
Product environmental attributes - Market requirements (continued)  Requirement met						t met
Item				Yes	No	n.a.

P7.21*   Biobased plastic material content is used in the product (See NOTE B7):		Material and subs	stance requirements	(continued)						
a) Of total plastic parts' weight > 25 g, the biobased plastic material content (calculated as a percentage of total plastic by weight) is 0 %.  P7.22* Light sources are free from mercury, i.e. less than 0,1 mg/lamp. If mercury is used specify: Number of lamps:  P8.1* Batteries  P9.1 For the product the following power levels or energy consumptions are reported:  Energy mode*  P9. Energy consumption (See NOTE 88)  P9.1 For the product the following power levels or energy consumptions are reported:  Energy mode *  Peak (On-max)  45 W  45 W  45 W  Full load  Category 1  Short Idle State - WOL  Enabled  1.74 W  1.64 W  1.68 W	P7.21*	Biobased plastic m	naterial content is used	d in the product (See N	NOTE B7):					
a) Of total plastic parts' weight > 25 g, the biobased plastic material content (calculated as a percentage of total plastic by weight) is 0 %.  P7.22* Light sources are free from mercury, i.e. less than 0,1 mg/lamp. If mercury is used specify: Number of lamps:  P8.1* Batteries  P9.1 For the product the following power levels or energy consumptions are reported:  Energy mode*  P9. Energy consumption (See NOTE 88)  P9.1 For the product the following power levels or energy consumptions are reported:  Energy mode *  Peak (On-max)  45 W  45 W  45 W  Full load  Category 1  Short Idle State - WOL  Enabled  1.74 W  1.64 W  1.68 W		If YES: at least one	e of the two alternative	es below shall be answ	vered:					
proper by The weight of the biobased plastic material is g.  P7.22 Light sources are free from mercury, i.e. less than 0,1 mg/lamp. If mercury is used specify. Number of lamps: and maximum mercury content per lamp: mg  P8. Batteries  P8.11 Battery chemical composition: LI-ION Polymer  P9 Energy consumption (See NOTE 88)  P9.1 For the product the following power levels or energy consumptions are reported:  Energy mode*  Power level at 100 V AC 115 V AC 230 V AC 745 W Full load  Category 1  Short Idle State - WOL 4.24 W 4.15 W 4.21 W Use for ENERGY STAR V8.0 registration (P <sub>rodio</sub> )  Sleep (S3) - WOL Enabled 0.50 W 0.51 W 0.43 W Use for ENERGY STAR V8.0 registration (P <sub>rodio</sub> )  Off (S5) - WOL Enabled 0.44 W 4.40 W 4.58 W Use for ENERGY STAR V8.0 registration (P <sub>rodio</sub> )  Sleep (S3) - WOL Enabled 0.50 W 0.51 W 0.43 W Use for ENERGY STAR V8.0 registration (P <sub>rodio</sub> )  Sleep (S3) - WOL Enabled 0.44 W 0.41 W 0.43 W Use for ENERGY STAR V8.0 registration (P <sub>rodio</sub> )  Sleep (S3) - WOL Enabled 0.44 W 0.41 W 0.43 W Use for ENERGY STAR V8.0 registration (P <sub>rodio</sub> )  Sleep (S3) - WOL Enabled 0.44 W 0.45 W Use for ENERGY STAR V8.0 registration (P <sub>rodio</sub> )  Sleep (S3) - WOL Enabled 0.44 W 0.45 W Use for ENERGY STAR V8.0 registration (P <sub>rodio</sub> )  Sleep (S3) - WOL Enabled 0.50 W 0.50 W 0.50 W 0.52 W Use for ENERGY STAR V8.0 registration (P <sub>rodio</sub> )  Sleep (S3) - WOL Enabled 0.50 W 0.50 W 0.52 W Use for ENERGY STAR V8.0 registration (P <sub>rodio</sub> )  Sleep (S3) - WOL Enabled 0.50 W 0.50 W 0.50 W 0.52 W Use for ENERGY STAR V8.0 registration (P <sub>rodio</sub> )  Sleep (S3) - WOL Enabled 0.50 W						ated as a percentage of				
b) The weight of the biobased plastic material is			y weight) is 0 %.							
P7.22   Light sources are free from mercury, i.e. less than 0.1 mg/lamp.   If mercury is used specify: Number of lamps:			the highered plactic	matarial is						
If mercury is used specify: Number of lamps:	P7 22*				<u> </u>	МПП				
P8	' ' ' ' ' '					er lamp: mg				
P9 Energy consumption (See NOTE B8) P9.1 For the product the following power levels or energy consumptions are reported: Energy mode * Power level at 100 V AC 115 V AC 230 V	P8	Batteries		•						
Post   For the product the following power levels or energy consumptions are reported:   Power level at 100 V AC	P8.1*	Battery chemical composition: <i>LI-ION Polymer</i>								
Power level at 100 V AC		Energy consumption (See NOTE B8)								
100 V AC										
Peak (On-max)         45 W         45 W         45 W         Full load           Category 1         Short Idle State - WOL Enabled         4.24 W         4.15 W         4.21 W         Use for ENERGY STAR V8.0 registration (P <sub>rimb</sub> )           Long Idle State - WOL Enabled         1.74 W         1.64 W         1.68 W         Use for ENERGY STAR V8.0 registration (P <sub>rimb</sub> )           Sleep (S3) - WOL Enabled         0.50 W         0.51 W         0.41 W         0.43 W         Use for ENERGY STAR V8.0 registration (P <sub>sites</sub> )           Off (S5) - WOL Enabled         0.41 W         0.41 W         0.43 W         Use for ENERGY STAR V8.0 registration (P <sub>sites</sub> )           Category 2         Short Idle State - WOL Enabled         4.42 W         4.40 W         4.58 W         Use for ENERGY STAR V8.0 registration (P <sub>sites</sub> )           Long Idle State - WOL Enabled         1.86 W         2.03 W         1.91 W         Use for ENERGY STAR V8.0 registration (P <sub>sites</sub> )           Sleep (S3) - WOL Enabled         0.50 W         0.50 W         0.52 W         Use for ENERGY STAR V8.0 registration (P <sub>sites</sub> )           Off (S5) - WOL Enabled         0.40 W         0.40 W         0.42 W         Use for ENERGY STAR V8.0 registration (P <sub>sites</sub> )           PTEC ** Typical Energy Consumption         W         W         W         W           ETEC ** Annual Energy Consumption	Energy mod	de *				0,				
Category 1	Poak (On-I	nav)								
Short Idle State - WOL   See for ENERGY STAR V8.0   registration (P <sub>Idle</sub> )	reak (OII-I	nax)	40 VV	70 VV	70 VV	T un rodu				
Enabled	Category	<u>/ 1</u>								
		State - WOL	4.24 W	4.15 W	4.21 W					
	Enabled					registration (P <sub>idle</sub> )				
Sleep (S3) - WOL Enabled  0.50 W  0.51 W  0.53 W  Use for ENERGY STAR V8.0 registration (P <sub>sleep</sub> )  Category 2  Short Idle State - WOL Enabled  1.86 W  2.03 W  1.91 W  Use for ENERGY STAR V8.0 registration (P <sub>olfl</sub> ) Use for ENERGY STAR V8.0 registration (P <sub>olfl</sub> )  Sleep (S3) - WOL Enabled  0.50 W  0.50 W  1.91 W  Use for ENERGY STAR V8.0 registration (P <sub>olfl</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>olfl</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>olfl</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>olfl</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>olfl</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>olfl</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>olfl</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>olfl</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>olfl</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>olfl</sub> ) Use for ErP  EPS No-load (External power supply / charger plugged in the product)  PTEC *  W  W  W  W  ETEC = (8760/1000) × (P <sub>olf</sub> × 0.25   15.75(Cat2)   15.75(Cat2)   15.75(Cat2)   15.75(Cat2)   15.22(Cat2)   15.75(Cat2)   15.22(Cat2)   15.75(Cat2)   15.22(Cat2)   15.75(Cat2)   15.25(Cat2)   15.25(Cat	Long Idle S	State - WOL	1.74 W	1.64 W	1.68 W	Use for ENERGY STAR V8.0				
	Enabled					registration (P <sub>idle</sub> )				
	Sleen (S3)	- WOL Fnabled	0.50 W	0 51 W	0.53 W	Use for ENERGY STAR V8.0				
Off (S5) - WOL Enabled  O.41 W  O.41 W  O.43 W  Use for ENERGY STAR V8.0 registration (Post) Use for EFP  Short Idle State - WOL Enabled  I.86 W  I.86 W  I.86 W  I.86 W  I.91 W  I.92 For ENERGY STAR V8.0 registration (Pidle)  Sleep (S3) - WOL Enabled  O.50 W  I.90 W  I.91 W  I.92 For ENERGY STAR V8.0 registration (Pidle)  I.93 W  I.94 W  I.95 W  I.	Greep (GG)	- WOL LINDICU	0.00 11	0.07 **	0.00 11					
Short Idle State - WOL Enabled  Long Idle State - WOL Enabled  1.86 W  2.03 W  1.91 W  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Sleep (S3) - WOL Enabled  0.50 W  0.50 W  0.50 W  0.52 W  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  Use for ENERGY STAR V8.0 registration (P <sub>Idlio</sub> )  U	Off (S5) - V	VOL Enabled	0.41 W	0.41 W	0.43 W					
Short Idle State - WOL Enabled  Long Idle State - WOL Enabled  1.86 W  2.03 W  1.91 W  Use for ENERGY STAR V8.0 registration (P <sub>Idle</sub> )  Sleep (S3) - WOL Enabled  0.50 W  0.50 W  0.50 W  Use for ENERGY STAR V8.0 registration (P <sub>Idle</sub> )  Wuse for ENERGY STAR V8.0 registration (P <sub>sleep</sub> )  Off (S5) - WOL Enabled  0.40 W  0.40 W  0.40 W  0.42 W  Use for ENERGY STAR V8.0 registration (P <sub>off</sub> ) Use for EPP  EPS No-load (External power supply / charger plugged in the well outlet but disconnected from the product.)  PTEC * Typical Energy Consumption  ETEC * Annual Energy Consumption  15.10(Cat1); 14.80(Cat1); 15.10(Cat1); 15.65(Cat2) kWh/year kWh/year kWh/year kWh/year  Pont: Off Mode(S5) - WOL Enabled; P <sub>sleep</sub> : Sleep Mode(S3) - WOL Enabled; P <sub>Idle</sub> : Idle State - WOL Enabled						registration (P <sub>off</sub> ) Use for ErP				
Enabledregistration ( $P_{idle}$ )Long Idle State - WOL Enabled1.86 W2.03 W1.91 WUse for ENERGY STAR V8.0 registration ( $P_{idle}$ )Sleep (S3) - WOL Enabled0.50 W0.50 W0.52 WUse for ENERGY STAR V8.0 registration ( $P_{sleep}$ )Off (S5) - WOL Enabled0.40 W0.40 W0.42 WUse for ENERGY STAR V8.0 registration ( $P_{off}$ ) Use for ErPEPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.)0.06 W0.06 WPTEC * Typical Energy ConsumptionWWWETEC * Annual Energy Consumption15.10(Cat1); 15.65(Cat2) kWh/year14.80(Cat1); 15.75(Cat2) kWh/year15.10(Cat1); 16.22(Cat2) kWh/yearETEC = (8760/1000) x ( $P_{off}$ x 0.25 + $P_{sleep}$ x 0.35 + $P_{long\_idle}$ x 0.10+ Pshort Idle x 0.30)Poil: Off Mode(S5) - WOL Enabled; $P_{sleep}$ : Sleep Mode(S3) - WOL Enabled; $P_{ldle}$ : Idle State - WOL Enabled	Category	<u>/ 2</u>								
Long Idle State - WOL Enabled  1.86 W 2.03 W 1.91 W Use for ENERGY STAR V8.0 registration (P <sub>idle</sub> )  Sleep (S3) - WOL Enabled  0.50 W 0.50 W 0.52 W Use for ENERGY STAR V8.0 registration (P <sub>steep</sub> )  Off (S5) - WOL Enabled  0.40 W 0.40 W 0.42 W Use for ENERGY STAR V8.0 registration (P <sub>off</sub> ) Use for ErP  EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.)  PTEC * Typical Energy Consumption  ETEC * Annual Energy Consumption  15.10(Cat1); 15.10(Cat1); 15.40(Cat1); 15.10(Cat1); 15.65(Cat2) kWh/year kWh/year kWh/year P <sub>short Idle</sub> x 0.30) P <sub>off</sub> : Off Mode(S5) - WOL Enabled; P <sub>sleep</sub> : Sleep Mode(S3) - WOL Enabled; P <sub>idle</sub> : Idle State - WOL Enabled	Short Idle	State - WOL	4.42 W	4.40 W	4.58 W	Use for ENERGY STAR V8.0				
Enabled  Sleep (S3) - WOL Enabled  0.50 W  0.50 W  0.52 W  Use for ENERGY STAR V8.0 registration (P <sub>sleep</sub> )  Off (S5) - WOL Enabled  0.40 W  0.40 W  0.40 W  Use for ENERGY STAR V8.0 registration (P <sub>off</sub> ) Use for ErP  EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product)  PTEC * Typical Energy Consumption  ETEC * Annual Energy Consumption  ETEC * Annual Energy Consumption  Isomorphise in the product in the product in the product in the product in the wall outlet but disconnected from the product in the	Enabled					registration (P <sub>idle</sub> )				
Enabled   Continue	Long Idle S	State - WOL	1.86 W	2.03 W	1.91 W	Use for ENERGY STAR V8.0				
registration (P <sub>sleep</sub> )         Off (S5) - WOL Enabled       0.40 W       0.42 W       Use for ENERGY STAR V8.0 registration (P <sub>off</sub> ) Use for ErP         EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.)       0.06 W       0.06 W         PTEC * Typical Energy Consumption       W       W       W         ETEC * Annual Energy Consumption       15.10(Cat1); 14.80(Cat1); 15.75(Cat2) 15.75(Cat2) 15.75(Cat2) 15.75(Cat2) 16.22(Cat2) 16.22(Cat2		J. 1702		2.00 11	1.01					
registration (P <sub>sleep</sub> )         Off (S5) - WOL Enabled       0.40 W       0.42 W       Use for ENERGY STAR V8.0 registration (P <sub>off</sub> ) Use for ErP         EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.)       0.06 W       0.06 W         PTEC * Typical Energy Consumption       W       W       W         ETEC * Annual Energy Consumption       15.10(Cat1); 14.80(Cat1); 15.75(Cat2) 15.75(Cat2) 15.75(Cat2) 15.75(Cat2) 15.75(Cat2) 16.22(Cat2) 16.22(Cat2	Cloop (C2)	WOL Enabled	0.50\\\	0.50.\//	0.52 \\/	Hos for ENERGY STAR VOA				
Off (S5) - WOL Enabled  0.40 W  0.40 W  0.40 W  Use for ENERGY STAR V8.0 registration (Port) Use for ErP  EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.)  PTEC * Typical Energy Consumption  ETEC * Annual Energy Consumption  15.10(Cat1); 14.80(Cat1); 15.10(Cat1); 15.65(Cat2) 15.75(Cat2) 15.75(Cat2) 16.22(Cat2) 16.22(C	Sieep (S3)	- WOL Enabled	0.50 VV	0.50 VV	0.52 VV					
EPS No-load   (External power supply / charger plugged in the wall outlet but disconnected from the product.)   W   W   W										
EPS No-load  (External power supply / charger plugged in the wall outlet but disconnected from the product.)  PTEC *  Typical Energy Consumption  ETEC *  Annual Energy Consumption  ### A	Off (S5) - V	VOL Enabled	<b>0.40</b> W	0.40 W	<b>0.42</b> W					
(External power supply / charger plugged in the wall outlet but disconnected from the product.)  PTEC * Typical Energy Consumption  ETEC * Annual Energy Consumption    15.10(Cat1);						registration (Poff) Use for ErP				
PTEC *         W         W         W           Typical Energy Consumption         15.10(Cat1);         14.80(Cat1);         15.10(Cat1);         16.22(Cat2)         16.22(Cat2)         15.10(Cat1);         15.10(Cat1);         16.22(Cat2)			0.06 W	0.06 W	0.06 W					
Typical Energy Consumption $ETEC^*$	(External power s wall outlet but disc	upply / charger plugged in the connected from the product.)								
ETEC *	PTEC *		W	W	W					
Annual Energy Consumption    15.65(Cat2)		ergy Consumption			1-1-1-1					
kWh/year kWh/year RWh/year Pshort Idle x 0.30)  Poff: Off Mode(S5) - WOL Enabled; Psleep: Sleep Mode(S3) - WOL Enabled; Pside: Idle State - WOL Enabled		aray Consumption								
Pott: Off Mode(S5) - WOL Enabled; Psleep: Sleep Mode(S3) - WOL Enabled; Pidle: Idle State - WOL Enabled	Alliluai Elle	ngy Consumption								
External Power Supply Efficiency Level (International Efficiency Marking Protocol) *: VI						ed; Pidle: Idle State - WOL Enabled				
	External Po	wer Supply Efficien	cy Level (Internationa	I Efficiency Marking Pr	rotocol) * : VI	· 🗆				
Display resolution *: 2.07 megapixels	Display res	olution * : 2.07 meg	apixels	-		1920*1080				
Default time to enter energy save mode: 7.5 minutes	Default time									
P9.2* Information about the energy save function is provided with the product.	P9.2*									
P9.3 Energy efficiency class (monitors only):	P9.3		0,		-					

NOTE B8 A Guidance document on Energy Efficiency is available;

see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B9 A Guidance document on Acoustic Noise is available;

see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

P10	Emissions						
	Noise emission – Declared according to ISO 9296 (See NOTE B9)						
P10.1	Mode	Mode description	Statistical upper limit A-weighted sound power level, L <sub>WA,c</sub> (B)				
Ì	Idle	* SSD:Idle	* 2.2				
ĺ	Operation	* SSD: Operating	* 2.7				
1	Other mode	Declared A-weighted sound pressure level (dB) $L_{p  m Am}$					
	Other mode	Declared A-weighted sound pressure level (dB) $L_{p  m Am}$	20 (operator position desktop – operating)				
	Measured according to: ☐ ISO 7779 ☐ ECMA-74						
		Other (only if not covered by ECMA-74)					

Model number	r* 82M7				Logo	Long	1/0	
Issue date *	2021-4-27					Leno	VO.	÷
Product envi	ironmental attributes	s - Market requirements (co	ntinued)			Require	ment	met
Item			•			Yes	No	n.a.
	ectromagnetic emission							
pro	gram(s): MPR-II(3 pin A		electromagnetic field:	s of the follo	wing voluntary			
	gonomics for computin							
		nomic requirements of ISO 9241	•		ies.	$\boxtimes$		
P12.2* The	e physical input device m	neets the requirements of ISO 99	95 and ISO 9241-41	0.				
	ckaging and document							
Pro Pro	Product packaging material type(s): Corrugated Fiberboard weight (kg): 0.27  Product packaging material type(s): PE weight (kg): 0.011  Product packaging material type(s): EPE weight (kg): 0.06  Product packaging material type(s): PP weight (kg): 0.003							
P13.2* Pro	oduct plastic primary pac	kaging is free from PVC.				X		
	r product primary corrug	gated fiberboard packaging, spe ontent: <b>100</b> %	ecify the contained p	percentage o	of minimum p	ost-		
		product documentation (tick box)	):					
Ele	ectronic 🔀, Paper 🔀, C	Other 🗌						
Ùse		item if paper documentation used tation on paper media is chlorine						
Tot	tally chlorine-free							
Ele	emental chlorine-free					$\overline{\boxtimes}$		
Pro	ocessed chlorine-free							
P14 Vo	luntary programs							
P14.1 The	e product meets the requ	irements of the following volunta	ry program(s):					
Ecc Ecc	ERGY STAR® o-label: o-label:	Criteria version: <b>8.0</b> Criteria version: Criteria version:	Date: 2021/4/29 Date: Date:	Product ca Product ca Product ca	ategory:			
	ditional information (Se							
		pecific configuration may vary						
info kno pro	ormation contained in this owledge available at the	representations, guarantees, ass s document. All information provi time of completion, and supplier te and provided for informational	ded by supplier in thi shall have no obligat	is document tion to updat	is provided ba e such informa	sed on suppation. The inf	olier's formati	ion
		Notebooks & Tablet Computers for ndex.cfm?fuseaction=find_a_pro			ode=CO			
	·	·						

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

## Legal references Europe Annex B2

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1
Regulation (EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7
Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances)	P1.3, P5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
Directive 2013/56/EC (Battery and accumulators Directive) *  * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) No 1272/2008 (CLP Regulation)	P7.19
Directive 2004/12/EC ( Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1

# Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

### **Products scope of this sheet:**

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	IdeaPad Flex 5 Chrome 13ITL6	Logo	
Model number *	82M7		Lonovo
Issue date *	2021-4-27		Lenovo.
Additional information			

d)	Year of manufacture:				2021
e)	Etec value (kWh) per ErP Lot 3 Catego disabled and if the system is tested with				cards (dGfx) are
(f) Etec value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete graphics cards (denable					cards (dGfx) are
		Category A (according to ErP Lot 3)	Category B (according to ErP Lot 3)	Category C (according to ErP Lot 3)	Category D (according to ErP Lot 3)
	Memory over base [GB]	4			
ents	Additional internal storage	No (Yes / No)	(Yes / No)	(Yes / No)	(Yes / No)
adjustm ring tes	Discrete television tuner	No (Yes / No)	(Yes / No)	(Yes / No)	(Yes / No)
capability adjustments applied during testing	Discrete Audio Card	No (Yes / No)	(Yes / No)	(Yes / No)	(Yes / No)
app	Discrete graphics Card(s) [number / #]	No #: (Yes / No)	#: (Yes / No)	#: (Yes / No)	#: (Yes / No)
	Category of discrete graphics Card(s)				
sults	Etec Value (kWh) - dGfx disabled all discrete graphics cards (dGfx) are disabled/ UMA is active for switchable graphics/ product has no graphics cards (dGfx)	5.90			
Test results	Etec Value (kWh) - dGfx enabled all discrete graphics cards (dGfx) are enabled				
)	Idle state power demand (Watts);				A : 1.15
)	Sleep mode power demand (Watts);				A : 0.59
	Sleep mode with WOL enabled power de	emand (Watts) (where	enabled);		A:NA
	Off mode power demand (Watts);				A : 0.45
)	Off mode with WOL enabled power dem	and (Watts) (where en	abled);		A : NA
)	Internal power supply aefficiency at 10 %	%, 20 %, 50 % and 100	% of rated output pov	wer (if applicable):	
	10% 20% 50%	100% Avera	age		
1)	External power supply efficiency (if appli	cable)*:			
	Average active efficiency: 87,98%,88,6	3%,88,83%			
	*internal note: show values for all available external p				
)	Minimum number of loading cycles that	the batteries can withs	tand (applies only to n	otebook computers):	300CYCLES
o-1)	Measurement methodology used to dete	ermine information mer <b>NA</b>	ntioned in points (I) – in	nternal PSU efficiency	:
)-2)	Measurement methodology used to dete			external PSU efficiend	cy:

(p-3)	Measurement methodology used to determine information mentioned in points (o) – loading cycles batteries:  EN 61960 measurement methodology						
(p-4)	Measurement metho power as defined in I	dology used to determine information mentioned in r Point P9.1 in the Product IT Eco Declaration:	naximum, idle, sleep, off mode				
		EN 62623:2013 measurement methodo	ology				
(q)	Sequence of steps for	or achieving a stable condition with respect to power	demand::				
	EN 62623:2013 measurement methodology						
(r)	Description of how s	Description of how sleep and/or off mode was selected or programmed:					
	EN 62623:2013 measurement methodology						
(s)	Sequence of events required to reach the mode where the equipment automatically changes to sleep and/or off mode:						
	refe	er to power management, 30mins automatically re	eaches sleep mode				
(t)		te condition before the computer automatically re a not exceed the applicable power demand requirement		8.5			
(u)	Length of time after	r a period of user inactivity in which the compute	r automatically reaches a power	NA			
(v)		ver power demand requirement than sleep mode (in ore the display sleep mode is set to activate after		7.5			
(w)		nergy-saving potential of power management function		7.0			
		refer to user manual					
(x)	User information on	how to enable the power management functionality:					
		refer to user manual					
(z)		measurements: — test voltage in V and frequency in system, — information and documentation on the institution.					
		230V, 50GHz, Total Harmonic Distortion	1 <2 %				
Addition	al Notebook Batter	y Information:					
		Battery[ies] <u>not</u> user replaceable	Battery[ies] user replaceable	n/a			
		The battery[ies] in this product cannot be easily replaced by users themselves. 1)					
Internal/b	ouilt-in Battery						
External/	detachable Battery						
Bios Bac	kup Battery						
Other:	Other:						
Additiona	Additional information						
)							
	1 the Alexander of Control of Control	9 1 11 0 0 1					

The battery[ies] in this product cannot be easily replaced by users themselves.

Акумулаторната[ите] батерия[и] в този продукт не може да се замени] посно от самите потребители.

Las baterías de este producto no pueden ser sustituidas fácilmente por los propios usuarios. Výměnu baterie/baterií v tomto výrobku by neměli provádět sami uživatelé.

Brugeren kan ikke uden videre udskifte batteriet/batterierne i dette produkt.

Der Akku/die Akkus dieses Produkts kann/können nicht ohne weiteres vom Benutzer selbst ausgetauscht werden. Kasutajad ei saa selle toote akut/akusid ise hõlpsasti asendada.

Η μπαταρία[-ες] στο προϊόν αυτό δεν μπορούν να αντικατασταθούν εύκολα από τους ίδιους τους χρήστες

La/les batterie(s présente(s) dans ce produit ne peuvent être facilement remplacée(s) par les utilisateurs eux-mêmes. Korisnik ne može lako zamijeniti Bateriju sam u ovom proizvodu.

La batteria/le batterie in questo prodotto non può/possono essere facilmente sostituita/e dall'utente. Lietotăji paši nevar nomainīt šā ražojuma akumulatoru(-us). Šio gaminio baterijos [baterijų] pats vartotojas negali lengvai pakeisti.

A termék akkumulátorát/akkumulátorait a felhasználó nem tudja egyedül egyszerűen kicserélni.

Il-batterija/batteriji f'dan il-prodott ma tistax/jistgħux tiġi/jiġu sostitwita/i mill-utenti stess. Batteriet [ene] i dette produktet kan ikke lett erstattes av brukerne selv.

De batterij(en) in dit product is (zijn) door de gebruiker niet gemakkelijk vervangbaar.

Użytkownik nie może sam w łatwy sposób wymienić baterii w tym produkcie. A ou as baterias deste produto não podem ser facilmente substituídas pelos próprios utilizadores.

Bateria (bateriile) din acest produs nu poate (pot) fi uşor înlocuită (înlocuite) de utilizatorii înşişi. Batériu(-ie) v tomto výrobku nemôže vymieňať používateľ. Baterij/baterije v tem izdelku uporabniki sami ne morejo zlahka zamenjati.

Tämän tuottéen akku [akut] ei[vät] ole helposti käyttäjän vaihdettavissa.

Det är inte enkelt för kunden att själv byta ut batteriet/batterierna. Bu üründeki batarya(lar) kullanıcılar tarafından kolaylıkla değiştirilemez.