



ECMA/TC38-TG3/2015/026 (Rev. 1 – 15 April 2015)

## Annex B2 - Product environmental attributes Notebooks and Tablets

The declaration may be published only when all rows and/or fields marked with \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

| Brand *                              | Lenovo   | Logo         |  |  |
|--------------------------------------|--|--------------|--|--|
| Company name *                       | Lenovo   | 1 . <u> </u> |  |  |
| Contact information * e-mail address | Lenovo Global Environmental Affairs Alvin L Carter alcarter@lenovo.com | Lenovo.      |  |  |
| Internet site *                      | http://www.lenovo.com/social_responsibility/us/en/environment          | .html        |  |  |
| Additional information               | The latest version of this document can be found at:                   |              |  |  |
|                                      | http://www.lenovo.com/ecodeclaration                                   |              |  |  |

| The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration. |  |  |  |  |  |
|--|--|--|--|--|--|
| Type of product *  | Notebook   |  |  |  |  |
| Commercial name *  | Legion 5 15 ACH6   |  |  |  |  |
| Model number *   | 82JW   |  |  |  |  |
| Issue date *   | 2020-04-03 (updated 05/2021)                                 |  |  |  |  |
| Intended market *  | ☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other |  |  |  |  |
| Additional information   |  |  |  |  |  |

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

#### About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template:

P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products

| Model nu   | mber *                             | 82JW   | Logo                            | Long        | N/6       |                        |
|------------|------------------------------------|--|---------------------------------|-------------|-----------|------------------------|
| Issue date | ) *                                | 2021-4-1   |                                 | Lend        | JVC       | <b>)</b> <sub>TH</sub> |
| Product    | environ                            | mental attributes - Legal requirements   |                                 | Require     | ment      | met                    |
| Item       |                                    |  |                                 | Yes         | No        | n.a.                   |
| P1         |                                    | ous substances and preparations  |                                 |             |           |                        |
| P1.1*      | Products                           | do comply with current European RoHS Directive. (See legal reference and NOTE  | EB1)                            | $\boxtimes$ |           |                        |
| P1.2*      |                                    | do not contain Asbestos (see legal reference).<br>ht: Legal reference has no maximum concentration value.  |                                 |             |           |                        |
| P1.3*      | Products<br>hydrobro<br>trichloroe | do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), smofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachethane, methyl bromide (see legal reference). Comment: Legal reference has no mation values.   |                                 |             |           |                        |
| P1.4*      |                                    | do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychel (PCT) in preparations (see legal reference).  | lorinated                       |             |           |                        |
| P1.5*      | Products                           | do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 car<br>ntaining at least 48% per mass of chlorine in the SCCP (see legal reference).   | bon atoms in tl                 | ne 🔀        |           |                        |
| P1.6*      | (see lega                          | h direct and prolonged skin contact do not release nickel in concentrations above (<br>al reference).<br>nt: Max limit in legal reference when tested according to EN1811:2011-5.  | ),5 μg/cm²/wee                  | ek 🔀        |           |                        |
| P1.7*      | REACH.                             | Article 33 information about substances in articles is available at (add URL or mail <a href="https://www.lenovo.com/us/en/Lenovo-REACH-SVHC-Disclosure">www.lenovo.com/us/en/Lenovo-REACH-SVHC-Disclosure</a>   | contact):                       | $\boxtimes$ |           |                        |
| P2         | Batteries                          |  |                                 |             |           |                        |
| P2.1*      |                                    | duct contains a battery or an accumulator, the battery/accumulator is labeled with<br>Information on proper disposal is provided in user manual. (See legal reference)   | the disposal                    |             |           |                        |
| P2.2*      | Batteries                          | s or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadne)  | nium. (See leg                  | al 🔀        |           |                        |
| P2.3*      | Batteries                          | and accumulators are readily removable. (See legal reference)  |                                 | $\boxtimes$ |           |                        |
| P3         | Conform                            | nity verification & Eco design (ErP)   |                                 |             |           |                        |
| P3.1*      | The D                              | duct is CE-marked to show conformance with applicable legal requirements (see legelaration of Conformity can be requested at (add link or e-<br>tyww.lenovo.com/us/en/compliance/eu-doc  | gal reference).<br>·mail addres |             |           |                        |
| P3.2*      |                                    | duct complies with the Eco design requirements for energy-related products, al reference).   |                                 |             |           |                        |
|            | Required                           | d information is; Sigiven in item P15 or added to this document, Significant and Significant Significa |                                 |             |           |                        |
| DE         |                                    | www.lenovo.com/us/en/compliance/eco-declaration  |                                 |             |           |                        |
| P5.1*      |                                    | packaging ng and packaging components do not contain more than 0,01% lead, mercur  | v cadmium o                     | nd 🔽        |           |                        |
|            | hexavale                           | ent chromium by weight of these together.  | , ,                             |             | <u> </u>  |                        |
| P5.2*      | used (se                           | kaging materials are marked with abbreviations and numbers indicating the nature e legal reference).   |                                 |             | <u> Ц</u> |                        |
| P5.3*      | (see lega                          | luct packaging material is free from ozone depleting substances as specified in the N<br>al reference).<br>nt: Legal reference has no maximum concentration values.  | Montreal Proto                  | col 🔀       |           |                        |
| P6         |                                    | nt information   |                                 |             |           |                        |
| P6.1*      |                                    | on for recyclers/treatment facilities is available (see legal reference).  |                                 | $\boxtimes$ |           |                        |

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

| Model number *        |            | 82JW   | Logo                        | Len         |               |              |
|-----------------------|------------|--|-----------------------------|-------------|---------------|--------------|
| Issue date * 2021-4-1 |            | 2021-4-1   |                             | Len         |               | TH           |
| Product               | environ    | mental attributes - Market requirements (See General NOTE GN   | below)                      |             |               |              |
|                       | - Enviro   | nmental conscious design   | ,                           | Require     | ment          | met          |
| Item                  |            | tory to fill in. Additional information regarding each item may be found under P14.  |                             | Yes         | No            | n.a.         |
| <b>P7</b> P7.1*       |            | Disassembly, recycling  It have to be treated separately are easily separable  |                             |             |               |              |
| P7.1*                 |            | naterials in covers/housing have no surface coating.   |                             |             |               | -            |
|                       |            | <u>~</u>   |                             |             |               | <del> </del> |
| P7.3*                 |            | arts > 100 g consist of one material or of easily separable materials.   |                             |             | <u> </u>      | <u> </u>     |
| P7.4*                 |            | arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.   | 2.11.6.1                    |             | <u> </u>      | <u> </u>     |
| P7.5                  |            | arts are free from metal inlays or have inlays that can be removed with commonly a   | valiable tools.             |             | <u>Ц</u>      | <u></u>      |
| P7.6*                 |            | re easily separable. (This requirement does not apply to safety/regulatory labels).  |                             |             |               |              |
| P7.7*                 | Product    |  |                             |             |               |              |
|                       |            | ng can be done e.g. with processor, memory, cards or drives  |                             |             | <del>  </del> |              |
| P7.8*                 |            | ng can be done using commonly available tools  |                             | $\boxtimes$ | Ш             | <u></u>      |
| P7.9                  |            | arts are available after end of production for: 3 years  |                             |             |               | <u>Ц</u>     |
| P7.10                 |            | s available after end of production for: 3 years   |                             |             |               |              |
| P7.11*                |            | and substance requirements cover/housing material type (e.g. plastics, metal, aluminum):   |                             |             |               |              |
| 77.11                 |            | type: <i>PC+ABS</i> Material type (e.g. plastics, filetal, aluminum).  |                             |             |               |              |
| P7.12                 |            | n materials of external electrical cables are PVC free.  |                             |             | $\square$     |              |
| P7.13                 | Insulation | n materials of internal electrical cables are PVC free.  |                             |             | X             | Ħ            |
| P7.14                 |            | plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) be   | romine and 0.1              | 1%          |               | $\dashv$     |
|                       | weight (   | 1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame  | retardants, a               | nd          | ш             |              |
|                       |            | chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in  | n parts containi            | ng          |               |              |
| P7.15                 |            | in 25% post-consumer recycled content.   |                             |             |               |              |
|                       | as define  | circuit boards, PCBs (without components) are low halogen: all 🔲 PCBs > 25 g 🦲 ed in IEC 61249-2-21. (See 1NOTE B2)                                  | are low halog               | en 🔲        |               |              |
| P7.16                 | Marking:   |  |                             |             |               |              |
| P7.17                 |            | hemical specifications of flame retardants in printed circuit boards > 25 g (without additive), TBBPA (reactive) (See NOTE B3), Other: , CAS #:      | ut component                | s):         |               |              |
|                       |            | nemical specifications of flame retardants in printed circuit boards (without compone  | ante) > 25 c                |             |               |              |
|                       |            | g ISO 1043-4: FR(16)   | /113) - 20 g                |             | ш             |              |
| P7.18                 | Alt. 1     |  |                             |             |               |              |
|                       |            | etarded plastic parts >25g contain the following flame retardant substances  | /preparations               | in          |               | _            |
|                       |            | ations above 0.1%:<br>ical name: CAS #:  |                             |             |               |              |
|                       | i. Cileiii | ical fiame. CAS #.   |                             |             |               |              |
|                       |            |  |                             |             |               |              |
|                       | Alt. 2     | 1 if the   |                             | _           | _             | _            |
|                       | FR(40)     | Il specifications of flame retardants in plastic parts >25g according ISO 1043-4:  |                             |             |               |              |
| P7.19                 |            | parts > 25 g, flame retardant substances/preparations above 0,1% are used which  | have been                   |             |               |              |
| F7.19                 |            | I the following Risk phrases; and Hazard statements: H411; H413  | nave been                   |             | Ш             | Ш            |
|                       |            | cce(s) for these classifications is/are found at (add URL(s)): European Count  | cil Directive               |             |               |              |
|                       | 67/548/E   | , , ,  |                             |             |               |              |
| P7.20*                |            | sumer recycled plastic material content is used in the product (See Note B6):  |                             |             | $\boxtimes$   |              |
|                       |            | t least one of the two alternatives below shall be answered;<br>otal plastic parts' weight > 25 g, the postconsumer recycled plastic material conten | t (calculated a             | 2           |               |              |
|                       |            | oral plastic parts, weight > 25 g, the posiconsumer recycled plastic material contemer<br>ercentage of total plastic by weight) is                   | i <sub>(</sub> valvulateu a | ,           |               |              |
|                       | or         |  |                             |             |               |              |
|                       | b) The     | weight of recycled material is g.  |                             |             |               |              |

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

| Model number *   | 82JW  | Leno |        | 21/0 |       |
|------------------|---|------|--------|------|-------|
| Issue date *     | 2021-4-1  |      | Len    |      | TH:   |
| Product environr | nental attributes - Market requirements (continued) |      | Requir | emen | t met |
| Item             |   |      | Yes    | No   | n.a.  |

|                   | Material and sub  | stance requirements                     | (continued)                |                            |  |  |  |  |  |
|-------------------|---|---|----------------------------|----------------------------|--|--|--|--|--|
| P7.21*            |   | material content is used                |                            | OTE B7):                   |  |  |  |  |  |
|                   | If VES: at least or   | ne of the two alternative               | es helow shall he answe    | ered.                      |  |  |  |  |  |
|                   |   | tic parts' weight > 25 g,               |                            |                            | ted as a percentage of   |  |  |  |  |
|                   | total plastic   |   | ,                          | ,                          |  |  |  |  |  |
|                   | or b) The weight of   | of the biobased plastic r               | material is a              |                            |  |  |  |  |  |
| P7.22*            |   | free from mercury, i.e.                 |                            |                            |  |  |  |  |  |
|                   |   | l specify: Number of lar                |                            | um mercury content pe      |  |  |  |  |  |
| P8                | Batteries   |   |                            |                            |  |  |  |  |  |
| P8.1*             | Battery chemical composition: <i>LI-ION Polymer battery and lithium-metal battery</i> |   |                            |                            |  |  |  |  |  |
| P9                |   | ption (See NOTE B8)                     |                            |                            |  |  |  |  |  |
| P9.1              |   | ne following power level                |                            |                            |  |  |  |  |  |
| Energy mo         | de *  | Power level at<br>100 V AC              | Power level at<br>115 V AC | Power level at<br>230 V AC | Reference/Standard for energy modes and test method *  |  |  |  |  |
| Peak (On-         | max)  | 230 W                                   | 230 W                      | 230 V AC                   | Full load  |  |  |  |  |
|                   |   |   |                            |                            |  |  |  |  |  |
| Categor           | <u>y 2</u>  |   |                            |                            |  |  |  |  |  |
| Short Idle        | State - WOL   | 10.77 W                                 | 10.71 W                    | 10.75 W                    | Reference  |  |  |  |  |
| Enabled           |   |   |                            |                            |  |  |  |  |  |
| Long Idle         | State - WOL   | 4.45 W                                  | 4.39 W                     | 4.44 W                     | Reference  |  |  |  |  |
| Enabled           |   |   |                            |                            | The form of the first of the fi |  |  |  |  |
|                   |   |   |                            |                            |  |  |  |  |  |
| Sleep (S3)        | - WOL Enabled   | <b>0.45</b> W                           | <b>0.45</b> W              | <b>0.47</b> W              | Reference  |  |  |  |  |
| Off (S5) - V      | WOL Enabled   | 0.35 W                                  | 0.35 W                     | 0.36 W                     | Reference  |  |  |  |  |
| Off (S5) - I      | WOL Disabled  | 0.35 W                                  | 0.35 W                     | 0.36 W                     | Use for ErP  |  |  |  |  |
| EPS No-loa        |   | 0.113 W                                 | 0.114 W                    | <b>0.115</b> W             |  |  |  |  |  |
| (External power s | supply / charger plugged in the connected from the product.)                          | •                                       |                            |                            |  |  |  |  |  |
| PTEC *            | connected from the product.)  | W                                       | W                          | W                          |  |  |  |  |  |
| Typical En        | ergy Consumption  |   |                            |                            |  |  |  |  |  |
| ETEC *            | ergy Consumption  | <b>34.35</b> kWh/year                   | <b>34.14</b> kWh/year      | <b>34.38</b> kWh/year      | $E_{TEC} = (8760/1000) \times (P_{off} \times 0.25 + P_{sleep} \times 0.35 + P_{long\_idle} \times 0.10 +$   |  |  |  |  |
| , annual Env      | orgy Corrodinption  |   |                            |                            | P <sub>short Idle</sub> x 0.30)  |  |  |  |  |
|                   |   |   |                            |                            | ed; Pidle: Idle State - WOL Enabled  |  |  |  |  |
| External Po       | ower Supply Efficie   | ncy Level (Internationa                 | I Efficiency Marking Pro   | otocol) * : VI             |  |  |  |  |  |
| Display res       | olution * : <b>2.07</b> meg   | gapixels                                |                            |                            |  |  |  |  |  |
| Default time      | e to enter energy s   | ave mode: 10 minutes                    |                            |                            |  |  |  |  |  |
| P9.2*             | Information about   | the energy save functi                  | on is provided with the    | product.                   |  |  |  |  |  |
| P9.3              | Energy efficiency   | class (monitors only):                  | <u>`</u>                   |                            |  |  |  |  |  |
| P10               | Emissions   |   |                            |                            |  |  |  |  |  |
|                   | Noise emission – Declared according to ISO 9296 (See NOTE B9)                         |   |                            |                            |  |  |  |  |  |
| P10.1             |   | Mode description                        |                            |                            | t A-weighted sound power level, L <sub>WA,c</sub> (B)  |  |  |  |  |
|                   | Idle  | * Idle (Operating)                      |                            | * 2.6                      |  |  |  |  |  |
|                   | Operation   | * HDD:Operation                         |                            | * NA(No HDD)               |  |  |  |  |  |
| }                 | Other mode  | CPU:Operation  Declared A-weighted soun | d pressure level (dB) I    | 5.1                        | sition desktop – idle)   |  |  |  |  |
| }                 |   | Declared A-weighted soun                |                            |                            | sition desktop – operating)  |  |  |  |  |
| 1                 |   |   |                            | (operator pos              | onen assittop – operating)   |  |  |  |  |
|                   | Measured accord   | · =                                     | ECMA-74                    |                            |  |  |  |  |  |
| 1                 | Other (only if not covered by ECMA-74)  |   |                            |                            |  |  |  |  |  |

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B9 A Guidance document on Acoustic Noise is available;  $see \ \underline{http://www.ecma-international.org/publications/standards/Ecma-370.htm}$ 

| Model number *                      | 82JW   | Logo                                  | Leno   | 1/0                |      |
|-------------------------------------|--|---------------------------------------|--|--------------------|------|
| Issue date *                        | 2021-4-1   |                                       | Lelio  | VO,                |      |
| Product enviro                      | nmental attributes - Market requirements (continued)   |                                       | Require  | ment               | met  |
| Item                                |  |                                       | Yes  | No                 | n.a. |
|                                     | omagnetic emissions  |                                       |  |                    |      |
| progra                              | uter display meets the requirement for low frequency electromagnetic fields of the<br>m(s): MPR-II(3 pin AC adapter only)  | following volunta                     | ary 🔀  |                    |      |
|                                     | omics for computing products   |                                       |  |                    |      |
|                                     | splay meets the ergonomic requirements of ISO 9241-307 for visual display technology   | ologies.                              | $\boxtimes$  |                    |      |
|                                     | hysical input device meets the requirements of ISO 9995 and ISO 9241-410.  |                                       | $\boxtimes$  |                    |      |
|                                     | ging and documentation   |                                       |  |                    |      |
| Produ<br>Produ<br>Produ             | ct packaging material type(s): Corrugated weight (kg): 0.49 ct packaging material type(s): paper(manual) weight (kg): 0.10 ct packaging material type(s): PP weight (kg): 0.016 ct packaging material type(s): PE weight (kg): 0.007 ct packaging material type(s): EPE weight (kg): 0.133 |                                       |  |                    |      |
| P13.2* Produ                        | ct plastic primary packaging is free from PVC.   |                                       | $\boxtimes$  |                    |      |
| P13.3* For pr                       | oduct primary corrugated fiberboard packaging, specify the contained percenta mer recovered fiber content: $100\ \%$   | ge of minimum                         | post-  |                    |      |
| P13.4* Specif                       | y media for user and product documentation (tick box):<br>onic ☑, Paper ☑, Other ☐   |                                       |  |                    |      |
| Ùser a                              | e only complete this item if paper documentation used) and product documentation on paper media is chlorine-free: please specify:  |                                       |  |                    |      |
| Eleme                               | r chlorine-free<br>ntal chlorine-free<br>ssed chlorine-free  |                                       |  |                    |      |
| P14 Volun                           | tary programs  |                                       |  |                    |      |
| P14.1 The p                         | roduct meets the requirements of the following voluntary program(s):   |                                       |  |                    |      |
| ENER<br>Eco-la                      |  | ct category:<br>ct category:          |  |                    |      |
| Eco-la                              | bel: Criteria version: Date: Produ-  | ct category:                          |  |                    |      |
|                                     | onal information (See NOTE B10)  |                                       |  |                    |      |
|                                     | y consumption of specific configuration may vary; description of the tested  |                                       |  |                    |      |
| inform<br>knowl<br>provid<br>inform |  | nent is provided<br>odate such infori | based on supposed in the based on supposed in the based on the based o | olier's<br>formati | on   |
|                                     | nergy Star Qualified Notebooks & Tablet Computers for the latest information: downloads.enerhttps://www.energystar.gov/products/office_equipment/computers   |                                       |  |                    |      |
|                                     |  |                                       |  |                    |      |

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

## Legal references Europe Annex B2

| Reference   | Declaration item       |
|---|------------------------|
| Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.  | P1.1                   |
| Regulation (EC) 1907/2006(REACH, Annex XVII   | P1.2, P1.4, P1.6, P1.7 |
| Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances)   | P1.3, P5.3             |
| Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002  | P1.5                   |
| Directive 2013/56/EC (Battery and accumulators Directive) *  * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.              | P2.1, P2.2, P2,3, P8.1 |
| Directive 2006/95/EC (Low Voltage Directive)  | P3.1                   |
| Directive 2004/108/EC (EMC Directive)   | P3.1                   |
| Directive 1999/5/EC (R&TTE Directive)   | P3.1                   |
| Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions | P3.1, P3.2             |
| Regulation (EC) No 1272/2008 (CLP Regulation)   | P7.19                  |
| Directive 2004/12/EC ( Packaging Directive)   | P5.1                   |
| Decision 97/129/EC (Secondary packaging legislation)  | P5.2                   |
| Directive 2012/19/EU (WEEE directive)   | P6.1                   |

# Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

### **Products scope of this sheet:**

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

| Commercial name *      | Legion 5 15ACH6 | Logo |         |
|------------------------|-----------------|------|---------|
| Model number *         | 82JW            |      | Lenovo  |
| Issue date *           | 2021-4-1        |      | renovo. |
| Additional information |                 |      |         |

| I)   | Year of manufacture:  |                                     |                                     |                                     | 2021                                |
|--|---|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|
| :)   | Etec value (kWh) per ErP Lot 3 Catego disabled and if the system is tested with   |                                     |                                     |                                     | cards (dGfx) are                    |
| )  | Etec value (kWh) per ErP Lot 3 Categor enable   | y and capability adjust             | ments applied when a                | Ill discrete graphics o             | cards (dGfx) are                    |
|  |   | Category A (according to ErP Lot 3) | Category B (according to ErP Lot 3) | Category C (according to ErP Lot 3) | Category D (according to ErP Lot 3) |
|  | Memory over base [GB]   |                                     |                                     | 32                                  |                                     |
| ents   | Additional internal storage   | (Yes / No)                          | (Yes / No)                          | yes<br>(Yes / No)                   | (Yes / No)                          |
| capability adjustments<br>applied during testing | Discrete television tuner   | (Yes / No)                          | (Yes / No)                          | No<br>(Yes / No)                    | (Yes / No)                          |
| ability a<br>lied du                             | Discrete Audio Card   | (Yes / No)                          | (Yes / No)                          | No<br>(Yes / No)                    | (Yes / No)                          |
|  | Discrete graphics Card(s) [number / #]  | #:<br>(Yes / No)                    | #:<br>(Yes / No)                    | Yes #: 1<br>(Yes / No)              | #:<br>(Yes / No)                    |
|  | Category of discrete graphics Card(s)   |                                     |                                     | G7                                  |                                     |
|  | Etec Value (kWh) - dGfx disabled<br>all discrete graphics cards (dGfx) are disabled/<br>UMA is active for switchable graphics/<br>product has no graphics cards (dGfx)                    |                                     |                                     |                                     |                                     |
| Test results                                     | Etec Value (kWh) - dGfx enabled all discrete graphics cards (dGfx) are enabled  |                                     |                                     | 13.97                               |                                     |
| )  | Idle state power demand (Watts);  | •                                   | <u> </u>                            | '                                   | 4.44                                |
| )  | Sleep mode power demand (Watts);  |                                     |                                     |                                     | 0.47                                |
|  | Sleep mode with WOL enabled power de  | emand (Watts) (where                | enabled);                           |                                     | 0.47                                |
|  | Off mode power demand (Watts);  |                                     |                                     |                                     | 0.36                                |
| )  | Off mode with WOL enabled power dema  | and (Watts) (where en               | abled);                             |                                     | 0.36                                |
|  | Internal power supply efficiency at 10 %,   | 20 %, 50 % and 100 °                | % of rated output pow               | er (if applicable):                 |                                     |
|  | 10% 20% 50%   | 100% Avera                          | ige                                 |                                     |                                     |
| 1)   | External power supply efficiency (if applie   | cable)*:                            |                                     |                                     |                                     |
|  | Average active efficiency: 93.33% 92.9  | 7%                                  |                                     |                                     |                                     |
| )  | *internal note: show values for all available external power supplies  Minimum number of loading cycles that the batteries can withstand (applies only to notebook computers):  300CYCLES |                                     |                                     |                                     |                                     |
| -1)  | Measurement methodology used to dete  | rmine information mer               | tioned in points (I) – in           | nternal PSU efficiency:             |                                     |

| (p-2)                       | Measurement methodology used to determine information mentioned in points (m) – external PSU efficiency:  ENERGY STAR® Program Requirements for Single Voltage External Ac-Dc and Ac-Ac Power Supplies  Eligibility Criteria (Version 2.0) |   |                                     |       |  |  |
|-----------------------------|--|---|-------------------------------------|-------|--|--|
| (p-3)                       | Measurement methodology used to determine information mentioned in points (o) – loading cycles batteries:  ≥70% of Cmin  |   |                                     |       |  |  |
| (p-4)                       |  | dology used to determine information mentioned in r<br>Point P9.1 in the Product IT Eco Declaration: <i>IEC</i> 626 |                                     |       |  |  |
| (q)                         | Sequence of steps for  | r achieving a stable condition with respect to power  | demand::                            |       |  |  |
|                             |  | Power on -> Wait 5 minutes -> Stable con  | ndition                             |       |  |  |
| (r)                         | Description of how sl  | eep and/or off mode was selected or programmed:   |                                     |       |  |  |
|                             |  | Begin menu -> Power -> Select sleep or o  | off mode                            |       |  |  |
| (s)                         | Sequence of events off mode:   | required to reach the mode where the equipment au   | tomatically changes to sleep and/or |       |  |  |
|                             |  | NA NA   |                                     |       |  |  |
| (t)                         |  | te condition before the computer automatically rent exceed the applicable power demand requirement                  |                                     | 30min |  |  |
| (u)                         | Length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes):  |   |                                     |       |  |  |
| (v)                         | Length of time before the display sleep mode is set to activate after user inactivity (in minutes):  |   |                                     |       |  |  |
| (w)                         | Information on the er  | ergy-saving potential of power management function  | nality: <i>Refer to User Guide</i>  |       |  |  |
| (x)                         | User information on I  | now to enable the power management functionality:   | Refer to User Guide                 |       |  |  |
| (z)                         |  | measurements: — test voltage in V and frequency in system, — information and documentation on the insting:          |                                     |       |  |  |
|                             |  | 230V50HZ-2%-Edition 2.0, 2011-01, Section 4   | 1, IEC62301                         |       |  |  |
| Addition                    | al Notebook Batter   | y Information:  |                                     |       |  |  |
|                             |  | Battery[ies] <u>not</u> user replaceable  | Battery[ies] user replaceable       | n/a   |  |  |
|                             |  | The battery[ies] in this product cannot be easily replaced by users themselves. $^{1)}$                             |                                     |       |  |  |
| Internal/b                  | uilt-in Battery  |   |                                     |       |  |  |
| External/detachable Battery |  |   |                                     |       |  |  |
| Bios Backup Battery         |  |   |                                     |       |  |  |
| Other:                      | Other:   |   |                                     |       |  |  |
| Additional                  | Additional information   |   |                                     |       |  |  |
|                             |  |   |                                     |       |  |  |
|                             |  |   |                                     |       |  |  |
| )                           |  |   |                                     |       |  |  |

The battery[ies] in this product cannot be easily replaced by users themselves.

Акумулаторната[ите] батерия[и] в този продукт не може да се замени[ят] лесно от самите потребители.

Výměnu baterie/baterií v tomto výrobku by neměli provádět sami uživatelé.

Brugeren kan ikke uden videre udskifte batteriet/batterierne i dette produkt.

Der Akku/die Akkus dieses Produkts kann/können nicht ohne weiteres vom Benutzer selbst ausgetauscht werden. Kasutajad ei saa selle toote akut/akusid ise hõlpsasti asendada.

Η μπαταρία[-ες] στο προϊόν αυτό δεν μπορούν να αντικατασταθούν εύκολα από τους ίδιους τους χρήστες

La/les batterie(s présente(s) dans ce produit ne peuvent être facilement remplacée(s) par les utilisateurs eux-mêmes. Korisnik ne može lako zamijeniti Bateriju sam u ovom proizvodu. La batteria/le batterie in questo prodotto non può/possono essere facilmente sostituita/e dall'utente.

Lietotāji paši nevar nomainīt šā ražojuma akumulatoru(-us). Šio gaminio baterijos [baterijų] pats vartotojas negali lengvai pakeisti. A termék akkumulátorát/akkumulátorait a felhasználó nem tudja egyedül egyszerűen kicserélni.

Il-batterija/batteriji f'dan il-prodott ma tistax/jistgħux tiġi/jiġu sostitwita/i mill-utenti stess. Batteriet [ene] i dette produktet kan ikke lett erstattes av brukerne selv.

De batterij(en) in dit product is (zijn) door de gebruiker niet gemakkelijk vervangbaar.

Użytkownik nie może sam w łatwy sposób wymienić baterii w tym produkcie. A ou as baterias deste produto não podem ser facilmente substituídas pelos próprios utilizadores.

Bateria (bateriile) din acest produs nu poate (pot) fi ușor înlocuită (înlocuite) de utilizatorii înșiși.

Batériu(-ie) v tomto výrobku nemôže vymieňať používateľ. Baterij/baterije v tem izdelku uporabniki sami ne morejo zlahka zamenjati.

Tämän tuotteen akku [akut] ei[vät] ole helposti käyttäjän vaihdettavissa.

Det är inte enkelt för kunden att själv byta ut batteriet/batterierna. Bu üründeki batarya(lar) kullanıcılar tarafından kolaylıkla değiştirilemez.