



ECMA/TC38-TG3/2015/026 (Rev. 1 – 15 April 2015)

## Annex B2 - Product environmental attributes Notebooks and Tablets

The declaration may be published only when all rows and/or fields marked with \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Lenovo	Logo
Company name *	Lenovo	
Contact information * e-mail address	Lenovo Global Environmental Affairs Alvin L Carter alcarter@lenovo.com	Lenovo
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment	t.html
Additional information	The latest version of this document can be found at:	
	http://www.lenovo.com/ecodeclaration	

	based on product specification or test results based obtained from sample testing), that the product nts given in this declaration.
Type of product *	Notebook
Commercial name *	ThinkPad X1 Extreme Gen 4; ThinkPad P1 Gen 4
Model number *	20Y5, 20Y6; 20Y3, 20Y4
Issue date *	2021/6/17
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other
Additional information	

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

#### About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template:

P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products

Model nu	mber *	20Y5, 20Y6; 20Y3, 20Y4	Logo	Long	21/0	
Issue date	e *	2021/6/17		Lend		тн
Product	environ	mental attributes - Legal requirements		Require	ment	met
Item				Yes	No	n.a.
P1		ous substances and preparations				
P1.1*		s do comply with current European RoHS Directive. (See legal reference and NOTE	B1)	$\boxtimes$		
P1.2*		s do not contain Asbestos (see legal reference). nt: Legal reference has no maximum concentration value.		$\boxtimes$		
P1.3*		s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),		$\boxtimes$		
	hydrobro trichloroe concentr	omofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrach ethane, methyl bromide (see legal reference). Comment: Legal reference has no m ration values.	naximum			
P1.4*		s do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polych l (PCT) in preparations (see legal reference).	lorinated			
P1.5*	Products	s do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carb ntaining at least 48% per mass of chlorine in the SCCP (see legal reference).	oon atoms in th	ne 🔀		
P1.6*	Parts wit	th direct and prolonged skin contact do not release nickel in concentrations above 0 al reference). In the contract of the con	,5 μg/cm²/wee	k 🔀		
P1.7*	REACH	Article 33 information about substances in articles is available at (add URL or mail www.lenovo.com/us/en/Lenovo-REACH-SVHC-Disclosure	contact):			
P2	Batterie					
P2.1*		educt contains a battery or an accumulator, the battery/accumulator is labeled with t Information on proper disposal is provided in user manual. (See legal reference)	he disposal			
P2.2*	Batteries	s or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadme)	nium. (See lega	al 🔀		
P2.3*	Batteries	and accumulators are readily removable. (See legal reference)		$\boxtimes$		
P3	Conforn	nity verification & Eco design (ErP)				
P3.1*	The prod The Dec	duct is CE-marked to show conformance with applicable legal requirements (see legal legal requirements) (see legal laration of Conformity can be requested at (add link or e-mail address):  www.lenovo.com/us/en/compliance/eu-doc for EU and  www.lenovo.com/us/en/compliance/uk-doc for UK	gal reference).			
P3.2*	The prod	duct complies with the Eco design requirements for energy-related products, al reference).		X		
	Required	d information is;				
P5		packaging				
P5.1*		ng and packaging components do not contain more than 0,01% lead, mercury	, cadmium a	nd 🔀		
P5.2*	hexavale	ent chromium by weight of these together.				
	used (se	kaging materials are marked with abbreviations and numbers indicating the nature e legal reference).				] [
P5.3*	(see lega	duct packaging material is free from ozone depleting substances as specified in the N al reference). nt: Legal reference has no maximum concentration values.	Montreal Protoc	ol 🔀		
P6		nt information				
P6.1*	Informati	on for recyclers/treatment facilities is available (see legal reference).		$\boxtimes$		

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model number *	20Y5, 20Y6; 20Y3, 20Y4	Logo	Lanova
Issue date *	2021/6/17		Lei IOVO.

- Environmental conscious design - "-mandatory to fill in. Additional information regarding each item may be found under P14. Yes No. n.a. P7 Design, Disassembly, recycling P7.1 Parts that have to be treated separately are easily separable P7.2. Plastic materials in covers/housing have no surface coating. P7.3 Plastic parts > 25 g pave material codes according to ISO 11469 referring ISO 1043-4. P7.5 Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. P7.6 Plastic parts set free from metal inlays or have inlays that can be removed with commonly available tools. P7.6 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.7 Plastic parts are available after end of production for 5 years P7.8 Upgrading can be done e.g. with processor, memory, cards or drives P7.9 Spare parts are available after end of production for 5 years P7.9 Spare parts are available after end of production for 5 years P7.1 Material and substance requirements P7.1 Material and substance requirements P7.1 Insulation materials of external electrical cables are PVC free. P7.1 Insulation materials of external electrical cables are PVC free. P7.1 Insulation materials of internal electrical cables are PVC free. P7.1 Insulation materials of external electrical cables are PVC free. P7.1 Insulation materials of external electrical cables are PVC free. P7.1 Insulation materials of external electrical cables are PVC free. P7.1 Insulation materials of external electrical cables are PVC free. P7.1 Insulation materials of external electrical cables are PVC free. P7.1 Insulation materials of external electrical cables are PVC free. P7.1 Insulation materials of external electrical cables are PVC free. P7.1 Insulation materials of external electrical cables are PVC free. P7.1 Insulation materials of external electrical cables are PVC free. P7.1 Insulation materials of external electrical cables are PVC free. P7.1 Insulation materials of external electrical cables are PVC fr	Produc	t environmental attributes - Market requirements (See General NOTE GN below)			
P7.11   Parts that have to be treated separately are easily separable	110000	- Environmental conscious design	Require	ment	met
P7.1   Parts that have to be freated separately are easily separable   P7.2   Plastic materials in covers/housing have no surface coating.   P7.3   Plastic parts > 100 g consist of one material or of easily separable materials.   P7.4   Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.   P7.5   Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.   P7.6   Labels are easily separable. (This requirement does not apply to safety/regulatory labels).   P7.7   Upgrading can be done e.g. with processor, memory, cards or drives   P7.8   Upgrading can be done using commonly available tools   P7.9   Spare parts are available after end of production for: 5 years   P7.10   Service is available after end of production for: 5 years   P7.10   Material and substance requirements   P7.11   Material yeb: CFRP / PC-GF   Material type: PCABS   Material type:			Yes	No	n.a.
P7.2* Plastic materials in covers/housing have no surface coating.  P7.3* Plastic parts > 100 g consist of one material or of easily separable materials.  P7.4* Plastic parts > 25 g have material codes according to ISO 11468 referring ISO 1043-4.  P7.5 Plastic parts > 25 g have material codes according to ISO 11468 referring ISO 1043-4.  P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.  P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels).  P7.7* Upgrading can be done e.g. with processor, memory, cards or drives  P7.7* Upgrading can be done e.g. with processor, memory, cards or drives  P7.8* Upgrading can be done using commonly available tools  P7.9 Spare parts are available after end of production for 5 years  Material and substance requirements  P7.10 Service is available after end of production for 5 years  Material and substance requirements  P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: CFRP / PC-GF  Material type: PCABS  P7.12 Insulation materials of external electrical cables are PVC free.  P7.13 Insulation materials of internal electrical cables are PVC free.  P7.14 External plastic casing/cover parts > 25 g contain no more than 0.1% weight (1000 ppm) bromine and 0.1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0.3% weight (3000 ppm) bromine and 0.3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content.  P7.16 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g ware low halogen as defined in IEC 51249-2-21. (See NHOTE B3). © Other-D0PO CAS #: 35948-25-5  Alt. 2: Chemical specifications of flame retardants in printed circuit boards × 25 g (without components) > 25 g according ISO 1043-4: FR(40)  P7.17 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparatio					
P7.3* Plastic parts > 100 g consist of one material or of easily separable materials.  P7.4* Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.  Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.  P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels).  P7.7* Upgrading can be done e.g. with processor, memory, cards or drives  P7.8* Upgrading can be done e.g. with processor, memory, cards or drives  P7.9* Spare parts are available after end of production for: 5 years  Material and substance requirements  P7.10* Service is available after end of production for: 5 years  Material and substance requirements  P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum):  Material type: PCABS  Material type		<u> </u>			
P7.4*   Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.   P7.5*   Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.   P7.6*   Labels are easily separable. (This requirement does not apply to safety/regulatory labels).   P7.7*   Upgrading can be done e.g., with processor, memory, cards or drives   P7.7*   Upgrading can be done e.g. with processor, memory, cards or drives   P7.8*   Upgrading can be done e.g. with processor, memory, cards or drives   P7.9*   Spare parts are available after end of production for: 5 years   P7.10*   Service is available after end of production for: 5 years   P7.11*   Product cover/housing material type (e.g. plastics, metal, aluminum): Material and substance requirements   P7.11*   Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: CFRP / PC+GF   Material type: PC/ABS   P7.12*   Insulation materials of internal electrical cables are PVC free.   P7.13*   Insulation materials of internal electrical cables are PVC free.   P7.14*   External plastic casing/cover parts > 25 g contain no more than 0.1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyviny chloride or 0.3% weight (3000 ppm) bromine and 0.3% weight (3000 ppm) phormine are low halogen: all PCBs > 25 g \( \) are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2)   P7.15*   P7.16*   P7.				<u> </u>	
P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.     P7.6   Labels are easily separable. (This requirement does not apply to safety/regulatory labels).    Product lifetime					
P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels).  Product lifetime  P7.7* Upgrading can be done e.g. with processor, memory, cards or drives  P7.8* Upgrading can be done e.g. with processor, memory, cards or drives  P7.9 Spare parts are available after end of production for: 5 years  P7.10 Service is available after end of production for: 5 years  Material and substance requirements  P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material and substance requirements  P7.12 Insulation materials of external electrical cables are PVC free.  P7.13 Insulation materials of internal electrical cables are PVC free.  P7.14 External plastic casing/cover parts > 25 g contain nore than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) bromine and 0,3% weight (1000 ppm) chlorine in parts containing more than 25% post-consumer recycled content.  P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g  are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2)  P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards > 25 g (without components):  TBBPA (additive). TBBPA (reactive) (See NOTE B3). Other: DOPO CAS #: 35948-25-5  Alt. 2. Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4:  P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%:  1. Chemical name: , CAS #:  3. Chemical apecifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40)  P7.19 In plastic parts > 25 g, flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40)  P7.19 In plastic parts > 25 g, flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40					
Product lifetime  P7.7* Upgrading can be done e.g. with processor, memory, cards or drives  P7.8* Upgrading can be done using commonly available tools  P7.9 Spare parts are available after end of production for: 5 years  P7.10 Service is available after end of production for: 5 years  Material type: CFRP / PC+OF  Material type: CFRP		Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.			
P7.7* Upgrading can be done e.g. with processor, memory, cards or drives  P7.8* Upgrading can be done using commonly available tools  P7.9 Spare parts are available after end of production for: 5 years  P7.10 Service is available after end of production for: 5 years  Material and substance requirements  P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material and substance requirements  P7.12 Insulation materials of external electrical cables are PVC free.  P7.13 Insulation materials of internal electrical cables are PVC free.  P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content.  P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g X are low halogen as defined in IEC 61494-2-21. (See 1NOTE B2)  P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: X Image: Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): Image: Alt. 1: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: X Image: Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: X Image: Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: X Image:	P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).			
P7.8° Upgrading can be done using commonly available tools P7.9 Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years    Material and substance requirements					
P7.9 Spare parts are available after end of production for: 5 years    P7.10 Service is available after end of production for: 5 years   P7.11			$\boxtimes$		
P7.10 Service is available after end of production for: 5 years    Material and substance requirements	P7.8*	Upgrading can be done using commonly available tools			
P7.11	P7.9	Spare parts are available after end of production for: 5 years			
P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: CFRP / PC+GF Material type: PC/ABS  P7.12 Insulation materials of external electrical cables are PVC free.  P7.13 Insulation materials of internal electrical cables are PVC free.  P7.14 External plastic casing/cover parts > 25 g contain no more than 0.1% weight (1000 ppm) bromine and 0.1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0.3% weight (3000 ppm) bromine and 0.3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content.  P7.15 Printed circuit boards, PCBs (without components) are low halogen: all □ PCBs > 25 g ☑ are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2)  P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:  Branking: FR(40)  P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components):  □ TBBPA (additive), □ TBBPA (reactive) (See NOTE B3), ☑ Other: DOPO CAS #: 35948-25-5  Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4:  P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%:  1. Chemical name: , CAS #:	P7.10	Service is available after end of production for: 5 years			
Material type: CFRP / PC+GF  Material type: PC/ABS  Material type: PC/ABS  P7.12 Insulation materials of external electrical cables are PVC free.  P7.13 Insulation materials of internal electrical cables are PVC free.  P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content.  P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g  are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2)  P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:					
P7.12 Insulation materials of external electrical cables are PVC free.  P7.13 Insulation materials of internal electrical cables are PVC free.  P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content.  P7.15 Printed circuit boards, PCBs (without components) are low halogen: all □ PCBs > 25 g \text{ are low halogen} \text{ as defined in IEC 61249-2-21. (See 1NOTE B2)}  P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: \text{ Marking: FR(40)}  P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): □ TBBPA (daditive), □ TBBPA (reactive) (See NOTE B3), ☑ Other: DOPO CAS #: 35948-25-5 ☑ □ □ □ Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □	P7.11*				
P7.13 Insulation materials of internal electrical cables are PVC free.  P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinade flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content.  P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2)  P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:  P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components):    TBBPA (additive),   TBBPA (reactive) (See NOTE B3),   Other: DOPO CAS #: 35948-25-5   Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4:  P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%:  1. Chemical name: , CAS #:	D7.40				
P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content.  P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2)  P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: FR(40)  P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive). TBBPA (reactive) (See NOTE B3). Other: DOPO CAS #: 35948-25-5  Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4:  P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%:  1. Chemical name: , CAS #: 3. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4. Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40)  P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5)  P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 3.33%.				<u> </u>	
weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content.  P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g  are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2)  P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:				_Ц_	
P7.15 Printed circuit boards, PCBs (without components) are low halogen: all □ PCBs > 25 g ☑ are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2)  P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:	P7.14	weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, an	d 💆		
as defined in IEC 61249-2-21. (See 1NOTE B2)  P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:  Marking: FR(40)  P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components):  TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other: DOPO CAS #: 35948-25-5  Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4:  P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%:  1. Chemical name: , CAS #: (See NOTE B4)  2. Chemical name: , CAS #: "  3. Chemical name: , CAS #: "  Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40)  P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5)  P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 3.33%.			g		
P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:  Marking: FR(40)  P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components):  □TBBPA (additive), □TBBPA (reactive) (See NOTE B3), ☑ Other: DOPO CAS #: 35948-25-5  Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4:  P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%:  1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40) □ P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements:  The source(s) for these classifications is/are found at (add URL(s)): , (See note B5)  P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6):  If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 3.33%.  or	P7.15		n 🛚		
TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other: DOPO CAS #: 35948-25-5  Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4:  P7.18  Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%:  1. Chemical name: , CAS #: (See NOTE B4)  2. Chemical name: , CAS #: "  3. Chemical name: , CAS #: "  Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40)  P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5)  P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 3.33%.  or	P7.16	Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: FR(40)	$\boxtimes$		
Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4:  P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%:  1. Chemical name: , CAS #: (See NOTE B4)  2. Chemical name: , CAS #: "  3. Chemical name: , CAS #: "  Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40)  P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5)  P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 3.33%.  or	P7.17				
P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%:  1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: "  Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40)  P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5)  P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 3.33%.  or		_ , , _ , _ , _ , _ , _ , _ , _ , _ , _			ш
concentrations above 0,1%:  1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: "  Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40)  P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)):  Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 3.33%.  or		· · · · · · · · · · · · · · · · · · ·			
1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: "  Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40)  P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5)  P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 3.33%.  or	P7.18	Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations i	n		
2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: "  Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40)  P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5)  P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 3.33%.  or		· ·			
3. Chemical name: , CAS #:   Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40)  P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)):  Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 3.33%.  or		, , , , , , , , , , , , , , , , , , , ,			
Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: FR(40)  P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)):  Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 3.33%.  or		,			
P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)):  Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 3.33%.  or		•			
assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)):  Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 3.33%.  or	DT 10			ᆜ	
The source(s) for these classifications is/are found at (add URL(s)): , (See note B5)  P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6):  If YES; at least one of the two alternatives below shall be answered;  a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 3.33%.  or	P7.19				Ш
P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6):  If YES; at least one of the two alternatives below shall be answered;  a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 3.33%.  or					
If YES; at least one of the two alternatives below shall be answered;  a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 3.33%.  or	D7 00*			_	
<ul> <li>a) Of total plastic parts' weight &gt; 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 3.33%.</li> <li>or</li> </ul>	P7.20*		$\boxtimes$	Ш	Ш
a percentage of total plastic by weight) is 3.33%. or					

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model number *	20Y5, 20Y6; 20Y3, 20Y4	Logo	Lanova
Issue date *	2021/6/17		Lei IOVO.

Product environmental attributes - Market requirements (continued)	Requir	emen	t met
Item	Yes	No	n.a.

D7 04*		stance requirements		OTE DZ):		_
P7.21*	Biobased plastic r	naterial content is use	ed in the product (See N	DIEB7):		Ш
	,		es below shall be answe	,		
			, the biobased plastic m	aterial content (calcula	ated as a percentage of	
	total plastic b	by weight) is %.				
		of the biobased plastic	material is q.			
P7.22*			less than 0,1 mg/lamp.		ΧП	
	If mercury is used	specify: Number of la	mps: and maxim	um mercury content p		
P8	Batteries					
P8.1*	Battery chemical	composition: Lithium	Ion/Lithium Manganes	e Dioxide		
P9		otion (See NOTE B8)				
P9.1			els or energy consumption			
Energy mo	ode *	Power level at	Power level at	Power level at	Reference/Standard for energy	
Darata (Ora		100 V AC	115 V AC	230 V AC	modes and test method *	
Peak (On-	·max)	<b>230</b> W	<b>230</b> W	<b>230</b> W	Full load	
Categor	v 2					
		47.0014	40.4014	40.474		
Short Idle Enabled	State - WOL	15.82W	16.10W	16.17W	Use for ENERGY STAR V8	
Enabled					registration (P <sub>idle</sub> )	
	State - WOL	1.56W	1.64W	1.62W	Use for ENERGY STAR V8	
Enabled					registration (P <sub>idle</sub> )	
		4 -0.44	1.001	4.0044		
Sieep (S3)	) - WOL Enabled	1.56W	1.64W	1.62W	Use for ENERGY STAR V8	
					registration (P <sub>sleep</sub> )	
Off (S5) -	WOL Enabled	<b>0.37</b> W	0.38W	<b>0.40</b> W	Use for ENERGY STAR V8	
					registration (P <sub>off</sub> )	
EPS No-lo	ad	0.10W	0.10 W	0.11 W		
(External power	supply / charger plugged in the					
ETEC *(2)	sconnected from the product.)	<b>48.53</b> kWh/year	49.64kWh/year	<b>49.76</b> kWh/year	$E_{TEC} = (8760/1000) \times (P_{off} \times 0.25 +$	
` '	ergy Consumption	40.00KVVII/yCai	43.04KVVII/yCai	43.7 0KVVII/yCai	$P_{sleep} \times 0.35 + P_{long\_ldle} \times 0.10+$	
,aa. <u>-</u>	iorgy consumption				P <sub>short Idle</sub> x 0.30)	
		Poff: Off Mode(S5) - W	/OL Enabled; P <sub>sleep</sub> : Sleep	Mode(S3) - WOL Enabl	led; P <sub>idle</sub> : Idle State - WOL Enabled	1
External P	ower Supply Efficie		al Efficiency Marking Pro			<u>'</u>
	solution * : <b>9.216</b> m	• '	, ,	,	3840*2400	┪
		ave mode: 10 minutes	<u> </u>		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	$\dashv$
P9.2*			tion is provided with the	product		+
P9.3		0,	uon is provided with the	product.		
		class (monitors only):				
P10	Emissions	Declared according	to ICO 0206 (Coo NOTE	: PO		
P10.1		Mode description	to ISO 9296 (See NOTE		nit A-weighted sound power level, $L_{WA,c}$	(R)
1 10.1		ldle mode		* 2.8	in A-weighted sound power level, LWA,c	(2)
		Operating (CPU)		* 4.2		<del>  </del>
	Operation '		nd propouro level (dD) -			
			nd pressure level (dB) $L_{pAm}$			
	Other mode	Declared A-weighted sou	nd pressure level (dB) $L_{p{\sf Am}}$	28 (operator position	on desktop – operating)	
	Measured accord	ing to: 🔀 ISO 7779	ECMA-74			
		Other	(only if not covered by	FCMA-74)		
	1		()st 5575754 by	· · · · /		

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B9 A Guidance document on Acoustic Noise is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

Model numi	ber *	20Y5, 20Y6; 2	20Y3, 20Y4				Logo	Lenc	1/0	
Issue date *	*	2021/6/17						Lenc	VO.	
Product er	nvironn	nental attribu	ites - Market requirem	nents (con	tinued)			Require	ment	met
Item					•			Yes	No	n.a.
		nagnetic emis								
	program(	(s): MPR-II(3 p	s the requirement for low fi in AC adapter only)	requency el	ectromagnetic field	s of the foll	owing voluntary	<i>y</i>		
P12 I	Ergonon	nics for comp	uting products							
			ergonomic requirements of				gies.	$\boxtimes$		
P12.2*	The phys	sical input devic	ce meets the requirements	of ISO 999	5 and ISO 9241-41	0.				
		ng and docum								
	Product p	packaging mate	erial type(s): corrugated erial type(s): paper erial type(s): LDPE	weight (kg weight (kg weight (kg	): <b>0.1</b>					
P13.2* I	Product p	plastic primary	packaging is free from PV	C.				$\boxtimes$		
	consume	r recovered fib	orrugated fiberboard pack er content: <b>65</b> %			oercentage	of minimum p	ost-		
		nedia for user a onic, ⊠Paper	and product documentation , Other	n (tick box):						
į į	Ùser and		his item if paper documen nentation on paper media							
	•	nlorine-free								
1		al chlorine-free ed chlorine-free	•							
P14 \	Voluntar	y programs								
			requirements of the followi	ing voluntar	y program(s):					
	Eco-labe Eco-labe Eco-labe	l: <b>TCO</b>	Criteria version: V8 Criteria version: IEEE 16 Criteria version: 14.0 Criteria version: Gen 8	680.1-2018	Date: 2021/6/17 Date: 2021/6/17 Date: 2021/6/17 Date: 2021/6/17	Product of Product of	category: <b>2</b> category: <b>Notel</b> category: <b>Notel</b> category: <b>Notel</b>	book		
			(See NOTE B10)							
P9	Energy o	consumption	of specific configuration	may vary;	description of the	tested pro	oduct configur	ration:		
	information knowledo provided information	on contained in ge available at here is approx on.	no representations, guara this document. All informathe the time of completion, and imate and provided for info	ation provid d supplier s ormational p	ed by supplier in th hall have no obligat ourposes only. See	is documer tion to upda a Lenovo <i>I</i>	nt is provided ba	ased on suppation. The in	olier's formati	on
P9 :	See Ene	rgy Star Qualifi w.energystar.g	ed Notebooks & Tablet Co ov/index.cfm?fuseaction=	omputers for find a prod	r the latest informat luct.showProductGi	ion: roup&pgw	code=CO			
	•									

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

## Legal references Europe Annex B2

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1
Regulation (EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7
Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances)	P1.3, P5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
Directive 2013/56/EC (Battery and accumulators Directive) *  * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) No 1272/2008 (CLP Regulation)	P7.19
Directive 2004/12/EC ( Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1

# Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

### **Products scope of this sheet:**

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	ThinkPad X1 Extreme Gen 4; ThinkPad P1 Gen 4	Logo	
Model Number	20Y5, 20Y6; 20Y3, 20Y4		Lonovo
Issue Date	2021/6/17		Lenovo.
Additional information			

d)	year of manufacture:				2021	
<del>)</del>	Etec value (kWh) per ErP Lot 3 Catego disabled and if the system is tested with	n switchable graphics n	node with UMA driving	g the display.		
)	Etec value (kWh) per ErP Lot 3 Categor enable	ry and capability adjust	tments applied when a	all discrete graphics	cards (dGfx) are	
		Category A (according to ErP Lot 3)	Category B (according to ErP Lot 3)	Category C (according to ErP Lot 3)	Category D (according to ErP Lot 3)	
	Memory over base [GB]	4		60		
ents ting	Additional internal storage	Yes (Yes / No)	(Yes / No)	Yes (Yes / No)	(Yes / No)	
capability adjustments applied during testing	Discrete television tuner	No (Yes / No)	(Yes / No)	No (Yes / No)	(Yes / No)	
ability a lied du	Discrete Audio Card	No (Yes / No)	(Yes / No)	No (Yes / No)	(Yes / No)	
caps	Discrete graphics Card(s) [number / #]	No #: (Yes / No)	#: (Yes / No)	Yes #: 1 (Yes / No)	#: (Yes / No)	
	Category of discrete graphics Card(s)					
sults	Etec Value (kWh) - dGfx disabled all discrete graphics cards (dGfx) are disabled/ UMA is active for switchable graphics/ product has no graphics cards (dGfx)	54.0		N/A		
Test results	Etec Value (kWh) - dGfx enabled all discrete graphics cards (dGfx) are enabled	N/A		148.5		
g)	Idle state power demand (Watts);				1.48	
1)	Sleep mode power demand (Watts);				1.48	
)	Sleep mode with WOL enabled power de	emand (Watts) (where	enabled);		1.48	
)	Off mode power demand (Watts);				0.36	
()	Off mode with WOL enabled power dem	and (Watts) (where en	abled);		0.36	
)	Internal power supply efficiency at 10 %,	, 20 %, 50 % and 100 °	% of rated output pow	er (if applicable):		
	10% 20% 50%	100% Avera	age			
n)	external power supply efficiency (if applie	cable)*:				
	Average active efficiency: 230W: 90.33	%,92.04%,91.91%,91.	21%			
	*internal note: show values for all available external p	ower supplies				
0)	Minimum number of loading cycles that the batteries can withstand (applies only to notebook computers): 300 cycles					
p-1)	Measurement methodology used to determine information mentioned in points (I) – internal PSU efficiency:  NA					
0-2)	Measurement methodology used to dete	ermine information mer	ntioned in points (m) –	external PSU efficience	CV.	

(p-3)	Measurement methodology used to determine information mentioned in points (o) – loading cycles batteries:  **IEC 61960 measurement methodology**				
(p-4)	Measurement methodology used to determine information mentioned in maximum, idle, sleep, off mode power as defined in Point P9.1 in the Product IT Eco Declaration:  IEC 62623 / IEC EN50564:2011 measurement methodology				
(q)	Sequence of steps for achieving a stable condition with respect to power demand::				
	IEC 62623 / IEC EN50564:2011 measurement methodology				
(r)	Description of how s	how sleep and/or off mode was selected or programmed:			
	refer to power management, sleep mode: ACPI system level G1/S3 (suspend to RAM) state; off mode: ACPI system level G2/S5 ('soft off') state				
(s)	Sequence of events required to reach the mode where the equipment automatically changes to sleep and/or off mode:				
	refer to power management, 10mins automatically reaches sleep mode				
(t)	Duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode (in minutes):			10 mins	
(u)	Length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes):			N/A	
(v)		re the display sleep mode is set to activate after		10 mins	
(w) Information on the energy-saving potential of power management functionality:				70 111110	
User information described in User Guide and Power Manager under ThinkVantage menu in all programs					
(x)	(x) user information on how to enable the power management functionality:				
User information described in User Guide and Power Manager under ThinkVantage menu in all programs					
(z)	z) test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing:  230V, 50GHz, Total Harmonic Distortion <2 %				
Additional Notebook Battery Information:					
Addition	al Notebook Batter	Battery[ies] <b>not</b> user replaceable	Battery[ies] user replaceable	n/a	
		The battery[ies] in this product cannot be easily replaced by users themselves. 1)	71 7		
Internal/built-in Battery					
External/detachable Battery					
Bios Backup Battery					
Other:					
Additional information					
L ) he hatten/lies in this product cannot be easily replaced by users themselves					

Акумулаторната[ите] батерия[и] в този продукт не може да се замени[ят] лесно от самите потребители.

Las baterías de este producto no pueden ser sustituidas fácilmente por los propios usuarios. Výměnu baterie/baterií v tomto výrobku by neměli provádět sami uživatelé.

Brugeren kan ikke uden videre udskifte batteriet/batterierne i dette produkt.

Der Akku/die Akkus dieses Produkts kann/können nicht ohne weiteres vom Benutzer selbst ausgetauscht werden. Kasutajad ei saa selle toote akut/akusid ise hõlpsasti asendada.

Η μπαταρία[-ες] στο προϊόν αυτό δεν μπορούν να αντικατασταθούν εύκολα από τους ίδιους τους χρήστες

La/les batterie(s présente(s) dans ce produit ne peuvent être facilement remplacée(s) par les utilisateurs eux-mêmes. Korisnik ne može lako zamijeniti Bateriju sam u ovom proizvodu.

La batteria/le batterie in questo prodotto non può/possono essere facilmente sostituita/e dall'utente. Lietotăji paši nevar nomainīt šā ražojuma akumulatoru(-us). Šio gaminio baterijos [baterijų] pats vartotojas negali lengvai pakeisti.

A termék akkumulátorát/akkumulátorait a felhasználó nem tudja egyedül egyszerűen kicserélni.

Il-batterija/batteriji f'dan il-prodott ma tistax/jistgħux tiġi/jiġu sostitwita/i mill-utenti stess. Batteriet [ene] i dette produktet kan ikke lett erstattes av brukerne selv.

De batterij(en) in dit product is (zijn) door de gebruiker niet gemakkelijk vervangbaar.

Użytkownik nie może sam w łatwy sposób wymienić baterii w tym produkcie. A ou as baterias deste produto não podem ser facilmente substituídas pelos próprios utilizadores.

Bateria (bateriile) din acest produs nu poate (pot) fi uşor înlocuită (înlocuite) de utilizatorii înşişi. Batériu(-ie) v tomto výrobku nemôže vymieňať používateľ. Baterii/baterije v tem izdelku uporabniki sami ne morejo zlahka zamenjati.

Tämän tuottéen akku [akut] ei[vät] ole helposti käyttäjän vaihdettavissa.

Det är inte enkelt för kunden att själv byta ut batteriet/batterierna. Bu üründeki batarya(lar) kullanıcılar tarafından kolaylıkla değiştirilemez.