

ECMA/TC38-TG3/2015/026 (Rev. 1 – 15 April 2015)

Annex B2 - Product environmental attributes Notebooks and Tablets

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Lenovo	Logo	
Company name *	Lenovo		
Contact information *	Lenovo Global Environmental Affairs		
e-mail address	Alvin L Carter	Lenovo	TM
	alcarter@lenovo.com		
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment	.html	
Additional information	The latest version of this document can be found at:		
	http://www.lenovo.com/ecodeclaration		

The company declares (based on product specification or test results based obtained from sample testing), that the product					
conforms to the statement	conforms to the statements given in this declaration.				
Type of product * Notebook					
Commercial name *	Yoga Slim 7 Pro 14ACH5 O, Yoga 14sACH 2021 O, Xiaoxin Pro 14 ACH5 O				
Model number *	82N5				
Issue date *	2021-3-24				
Intended market *	🛛 Global 📃 Europe 🗌 Asia, Pacific & Japan 🗌 Americas 🗌 Other				
Additional information					

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template:

P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products.

Model nu	mber *	82N5	Logo	Long		
Issue dat	e *	2021-3-24		Lend		
Product	environ	mental attributes - Legal requirements		Require	men	t met
Item		• ·		Yes	No	n.a.
P1	Hazardo	ous substances and preparations				
P1.1*	Products	s do comply with current European RoHS Directive. (See legal reference and NOTE	EB1)	\times		
P1.2*		s do not contain Asbestos (see legal reference). nt: Legal reference has no maximum concentration value.		\boxtimes		
P1.3*	Products hydrobro trichloro	s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), omofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrach ethane, methyl bromide (see legal reference). Comment: Legal reference has no m ration values.				
P1.4*		s do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polych /l (PCT) in preparations (see legal reference).	lorinated	\boxtimes		
P1.5*	Products chain co	s do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 cart ntaining at least 48% per mass of chlorine in the SCCP (see legal reference).				
P1.6*	Parts wi (see leg	th direct and prolonged skin contact do not release nickel in concentrations above 0 al reference). nt: Max limit in legal reference when tested according to EN1811:2011-5.),5 μg/cm²/week			
P1.7*		Article 33 information about substances in articles is available at (add URL or mail ovww.lenovo.com/us/en/Lenovo-REACH-SVHC-Disclosure	contact):	\boxtimes		
P2	Batterie	S				
P2.1*		oduct contains a battery or an accumulator, the battery/accumulator is labeled with t Information on proper disposal is provided in user manual. (See legal reference)	the disposal	\boxtimes		
P2.2*	Batteries	s or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadme)	nium. (See lega			
P2.3*	Batteries	s and accumulators are readily removable. (See legal reference)		\square		
P3	Conform	nity verification & Eco design (ErP)				
P3.1*	The proo	duct is CE-marked to show conformance with applicable legal requirements (see leg	gal reference). -mail address):		
P3.2*		duct complies with the Eco design requirements for energy-related products, al reference).		\boxtimes		
	Require	d information is; given in item P15 or added to this document, available at (add URL):				
		www.lenovo.com/us/en/compliance/eco-declaration				
P5		t packaging				
P5.1*	hexavale	ng and packaging components do not contain more than 0,01% lead, mercury ent chromium by weight of these together.	-			
P5.2*	used (se	kaging materials are marked with abbreviations and numbers indicating the nature one legal reference).				
P5.3*	(see leg	duct packaging material is free from ozone depleting substances as specified in the N al reference). nt: Legal reference has no maximum concentration values.	Iontreal Protoco	ol 🔀		
P6		nt information				
P6.1*		on for recyclers/treatment facilities is available (see legal reference).				

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Itesu date 2021-3-24 Lenovo. Product environmental attributes - Market requirements (See General NOTE GN below) Requirement met · *mandadoy to Blin - Additional information regarding each item may be found under P14. Yes No. n.a. PTO Design, Disassembly, recycling Image: Comparison on sufface cading. Image: Comparison sufface cading. Image: Comparison on s	Model nu	umber *	82N5	Logo	1.000		
- Environmental conscious design Requirement met Primatory to fill in Additional information regarding each term may be found under P14. Yes No n.a. P71 Parts that have to be treated separately are easily separable Image: Construction of the cons	Issue da	te *	2021-3-24		Len	ovo	Этн
Tem **mandatory to fill in. Additional information regarding each item may be found under P14. Yes No. n.a. P7 Design, Disassembly, recycling Image: Comparison of the treated separately are easily separable Image: Comparison of the treated separately are easily separable materials. Image: Comparison of the treated separately are easily separable materials. Image: Comparison of the treated separately are easily separable materials. Image: Comparison of the treated separately are easily separable materials. Image: Comparison of the treated separately are easily separable materials. Image: Comparison of the treated separately are easily separable materials. Image: Comparison of the treated separately are easily separable treated are treated work with the treated separately regulatory labels). Image: Comparison of treated separately are easily separable (This requirement does not apply to safety/regulatory labels). Image: Comparison of treated separately are easily separable treated are treated separately regulated separately regulated separately are asily aspectific treated separately are easily separately are asily separately are asily aspectific treated separately are easily separately are easily separately are easily separately regulated separately regulated separately regulated separately regulated separately are easily separately are asily separately are easily separately tables are easily separately regulated separately regulated separately regulated separately regulated separately and asset are easily separately regulated separately and asset are easily separately regulated separately at the separately asset are easily separately regulated separately asset are easily separately asset are easily separately regulated separately asset are e	Product						
P71 Design, Disassembly, recycling P71 Plastic materials in covers/housing have no surface coating. Image: Construction of the coating o							met
P7.1 Practs that have to be treated separately are easily separable Image: Control of Control					Yes	No	n.a.
P7.2* Plastic materials in coversitousing have no surface cealing. □ P7.3* Plastic parts > 100 g consist of one material or of easily separable materials. □ P7.4* Plastic parts > 25 g have material codes according to 105 11469 referring ISO 1043-4. □ P7.6* Lables are casily separable. (This requirement does not apply to safely/regulatory labels). □ P7.6* Lables are easily separable. (This requirement does not apply to safely/regulatory labels). □ P7.7* Upgrading can be done e.g. with processor, memory. cards or drives □ P7.7* Upgrading can be done e.g. with processor, memory. cards or drives □ P7.7* Variation materials of production for: 5 years □ P7.10 Service is available after end of production for: 5 years □ P7.11 Product coverhousing material type (.g. plastic/PC+ABS) □ P7.12 Insulation materials of external electrical cables are PVC free. □ P7.13 Insulation materials of external electrical cables are PVC free. □ P7.14 External plastic parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0.1% weight (1000 ppm) chorine at phastory and parts containing more than 25% post-xcharms response company end weight (2000 ppm) chorine in parts containing more than 25% post-xcharms, chorinated flame reta							
P7.3* Plastic parts > 100 g consist of one material or of easily separable materials. Image: Constraint of the c							<u> </u>
P7.4* Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. Image: Context in the context in the image: Context in the context							
P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. □ P7.6 Labels are easily separable. (This requirement does not apply to safety/regulatory labels). □ P7.7 Upgrading can be done e.g. with processor, memory, cards or drives ○ P7.8 Upgrading can be done e.g. with processor, memory, cards or drives ○ P7.8 Spare parts are available after end of production for: 5 years ○ Material and substance requirements ○ ○ P7.11 Product cover/housing material type: <i>instic/(PC+ABS)</i> ○ P7.12 Insulation materials of external electrical cables are PVC free. ○ ○ P7.14 External plastic casing/cover parts > 25 g contain no more than 0.1% weight (1000 ppm) bromine and 0.1% weight (1000 ppm) chorine attributable to brominated flame retardants, and polyviny! choride or 0.3% weight (3000 ppm) chorine and 0.1% weight (1000 ppm) bromine and 0.1% weight (1000 ppm) chorine in parts containing more than 25% post-consumer recycled content. ○ □ P7.14 External plastic casilo parts > 25 g on lant no more than 0.1% weight (1000 ppm) bromine and 0.1% □ P7.14 External plastic casilo parts > 25 g on lant no more than 0.1% weight (10000 ppm) bromine and 0.1% □		-					\square
P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). □ P7.7 Upgrading can be done e.g. with processor, memory, cards or drives □ P7.8* Upgrading can be done e.g. with processor, memory, cards or drives □ P7.9* Spare parts are available after end of production for: 5 years □ P7.10 Service is available after end of production for: 5 years □ P7.11* Product cover/housing material byte (e.g. plastic, metal, aluminum); Material type: aluminum Material type: grassic(PC+ABS) P7.11 Product cover/housing materials of internal electrical cables are PVC free. □ P7.13 Insulation materials of internal electrical cables are PVC free. □ P7.14 External plastic casing/cover parts > 25 g contain no more than 0.1% weight (1000 ppm) bromine and 0.1% weight (1000 ppm) choine artificable to brominated flame retardants, choinated flame retardants, and polyviny choinde or 0.3% weight (3000 ppm) comine and 0.3% weight (3000 ppm) choine in parts containing more than 25% part-consumer recycled content. P7.16 Filame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: □ P7.17 Att 1: Chemical specifications of flame retardants in printed circuit boards > 25 g weight (300 ppm) choine artificable > 25 g according ISO 1043-4: □ P7.18 Att 1	P7.4*	Plastic p	arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.		\square		
Product lifetime Image: Second S	P7.5	Plastic p	arts are free from metal inlays or have inlays that can be removed with commonly	available tools.	\boxtimes		
P7.7 Upgrading can be done e.g. with processor, memory, cards or drives □ P7.8 Upgrading can be done using commonly available tools □ P7.9 Spare parts are available after end of production for: 5 years □ P7.10 Service is available after end of production for: 5 years □ P7.11 Product cover/housing material type: plastic(PC+4BS) P7.12 Insulation materials of internal electrical cables are PVC free. □ P7.13 Insulation materials of internal electrical cables are PVC free. □ P7.14 External plastic casing/cover parts > 25 g contain no more than 0.1% weight (1000 ppm) bromine and 0.1% weight (1000 ppm) chorine at mbudable to brominated flame retardants, chlorinated flame retardants, and polyvinyi chloride or 0.3% weight (3000 ppm) bromine and 0.3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. □ P7.15 Printed circuit boards, PCBs (without components) are low halogen: all □ PCBs > 25 g □ are low halogen as defined in IEC 61249-22.1. (See INOTE B2) □ P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: □ P7.17 Alt 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): □ □ P7.18 Alt 1 Chemical plastic parts > 25g contain the following flame retardant	P7.6*	Labels a	re easily separable. (This requirement does not apply to safety/regulatory labels).		\boxtimes		
P7.8' Upgrading can be done using commonly available tools □ P7.9 Spare parts are available after end of production for: 5 years □ P7.10 Service is available after end of production for: 5 years □ Material and substance requirements □ P7.11 Product cover/housing material type: (basilic/(C+ABS)) P7.12 Insulation materials of external electrical cables are PVC free. □ P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine in partice on 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) bromine and 0,1% weight (1000 ppm) chlorine in partice on 0,3% weight (3000 ppm) chlorine in partice containing P7.15 Printed circuit boards, PCBs (without components) are low halogen: all □ PCBs > 25 g □ are low halogen as defined in IEC 61249-221. (See 1NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: □ P7.16 Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentralions above 0.1%: □ P7.16 Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentralions above 0.1%: □ P7.17 Alt 1_Chemical specifications of flame retardants in printed circuit boards (without components): □ □		Product	lifetime				
P7.9 Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11 Product cover/housing material kpe (e.g. plastic/PC+ABS) P7.12 Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0.1% weight (1000 ppm) bromine and 0.1% weight (1000 ppm) obtionine attributable to brominated filme retardants, chlorinated flame retardants, and polytinyl chloride or 0.3% weight (3000 ppm) bromine and 0.3% weight (3000 ppm) chlorine than 25% post-consumer recycled content. P7.16 Printed circuit boards, PCBs (without components) are low halogen: all □ PCBs > 25 g □ are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: P7.17 Att. 1; Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): □ P7.18 Att. 1 Flame retarded plastic parts >25 g contain the following flame retardant substances/preparations in concentrations above 0.1%: Chemical name: CAS #: 3. Chemical name: CAS #: 4.1 Flame retarded plastic parts >25g contain the following flame retar	P7.7*	Upgradir	ng can be done e.g. with processor, memory, cards or drives		\boxtimes		
P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11* Product coverhousing material type (e.g. plastics, metal, aluminum); Material type: aluminium Material and substance requirements P7.12 Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyviny chloride or 0.3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all □ PCBs > 25 g □ are low halogen as defined in IEC 61249-2:1. (See 1NOTE B2) P7.17 Alt 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): □ TBBPA (additive), □ TBBPA (reactive) (See NOTE B3), ○ Other: Brominated Epoxy Resins, CAS #: 26265-08-7 Alt: 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Chemical aneme: CAS #:<	P7.8*	Upgradir	ng can be done using commonly available tools		\boxtimes		
P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11* Product coverhousing material type (e.g. plastics, metal, aluminum); Material type: aluminium Material and substance requirements P7.12 Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyviny chloride or 0.3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all □ PCBs > 25 g □ are low halogen as defined in IEC 61249-2:1. (See 1NOTE B2) P7.17 Alt 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): □ TBBPA (additive), □ TBBPA (reactive) (See NOTE B3), ○ Other: Brominated Epoxy Resins, CAS #: 26265-08-7 Alt: 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Chemical aneme: CAS #:<	P7.9	Spare pa	arts are available after end of production for: 5 years				
Material and substance requirements P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: adminium Material type: adminium Material type: apastic(PC+ABS) P7.12 Insulation materials of atternal electrical cables are PVC free. Image: adminium P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) choine and 0,1% weight (1000 ppm) choine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl choirde or 0.3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) choine in parts containing P7.15 Printed circuit boards, PCBs (without components) are low halogen: all □ PCBs > 25 g □ are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: <i>FR4(0)</i> □ P7.17 Alt 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): □ P7.18 Alt 1: Chemical apecifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt 1: Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: CAS #: 3. Chemical name: CAS #: 4. Chemical	P7.10						<u> </u>
P7.11* Product over/housing material type (e.g. plastics, metal, aluminum); Material type: aluminum Insulation materials of external electrical cables are PVC free. Image: comparison of the plastic casing/cover parts > 25 g contain no more than 0.1% weight (1000 ppm) chorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl choride or 0.3% weight (3000 ppm) chorine attributable to brominate of flame retardants, chlorinated flame retardants, and polyvinyl choride or 0.3% weight (3000 ppm) bromine and 0.3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all □ PCBs > 25 g □ are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2) P7.16 Filme retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: P7.17 Alt 1; Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): P7.17 TBBPA (additive). TBBPA (additive). TBBPA (reactive) (See NOTE B3). Q themical specifications of flame retardants in printed circuit boards > 25 g according ISO 1043-4: P7.18 Filme retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Chemical apecifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt 1 1. Chemical apecifications of flame retardants in printed circuit boards (without components) >	-						
Material type: aluminum Material type: plastic(PC+ABS) P7.12 Insulation materials of external electrical cables are PVC free. Image: Comparison of the electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bronine and 0,1% weight (1000 ppm) chlorine atributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all [] PCBs > 25 g [] are low halogen as defined in IEC 61249-221. (See 1NOTE B2) P7.16 Filame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: P7.16 Filame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: P7.17 Att 1; Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): [] R26265-08-7 P7.18 Att. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: CAS #: 3. Chemical name: CAS #: 4. Chemical name: CAS #: 4. Chemical name: CAS #:	P7.11*						
P7.13 Insulation materials of internal electrical cables are PVC free. □ P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) choirne attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) choirne in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all □ PCBs > 25 g □ are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2) □ P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: □ P7.17 Alt 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): □ P7.18 Alt 1: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: □ P7.18 Alt 1: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: □ P7.18 Alt 1: Chemical name: CAS #: □ P7.18 Alt 1: □ □ 1			• • • • • • •				
P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chorine attributable to brominated flame retardants, chionicated flame retardants, and poly/myl chloride or 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all □ PCBs > 25 g □ are low halogen □ □ P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: □ P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): □ □ P7.18 RI. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): □ □ P7.18 Alt. 1: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: □ P7.18 Alt. 1 □ □ R1. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: □ P7.18 Alt. 1 □ □ R1. 1 Flame retarded plastic parts >25 g contain the following flame retardant substances/preparations in concentrations above 0.1%: □ Comment: No legal limits exist, this is a market requirement. 1. Chemical name: CAS #: □ Alt. 2 </td <td>P7.12</td> <td>Insulatio</td> <td>n materials of external electrical cables are PVC free.</td> <td></td> <td></td> <td>\boxtimes</td> <td></td>	P7.12	Insulatio	n materials of external electrical cables are PVC free.			\boxtimes	
weight (1000 ppm) chlorine attributable to brominated fiame retardants, chlorinated fiame retardants, and polyvnyl chloride or 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See INOTE B2) Image: FR(40) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: FR(40) Image: FR(40) P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive). ITBBPA (reactive) (See NOTE B3). QOther: Brominated Epoxy Resins, CAS #:	P7.13	Insulatio	n materials of internal electrical cables are PVC free.			$\overline{\mathbf{X}}$	
weight (1000 ppm) chlorine attributable to brominated fiame retardants, chlorinated fiame retardants, and polyvnyl chloride or 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See INOTE B2) Image: FR(40) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: FR(40) Image: FR(40) P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive). ITBBPA (reactive) (See NOTE B3). QOther: Brominated Epoxy Resins, CAS #:	P7.14	External	plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) b	promine and 0,1%		Ē	
P7.15 Printed circuit boards, PCBs (without components) are low halogen: all □ PCBs > 25 g □ are low halogen as defined in IEC 61249-221. (See INOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: <i>FR</i> (40) P7.17 Alt 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): □ TBBPA (additive), □ TBBPA (reactive) (See NOTE B3), ○ Other: <i>Brominated Epoxy Resins</i> , CAS #: 26265-08-7 Alt 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: CAS #: 3. Chemical name: CAS #: 4. Chemical name: CAS #: 4. Chemical name: CAS #: Alt 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0.1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20' Postconsumer recycled plastic material content is used in the product (See Note B6): If Y		weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flam	e retardants, and	- L		
P7.15 Printed circuit boards, PCBs (without components) are low halogen: all □ PCBs > 25 g □ are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: <i>FR(40)</i> P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): □ TBBPA (additive), □ TBBPA (reactive) (See NOTE B3), ○ Other: <i>Brominated Epoxy Resins</i> , CAS #: 2625-08-7 Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1 Rlame retarded plastic parts >25 g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: CAS #: 2. Chemical name: CAS #: 3. Chemical name: CAS #: 4. Chemical name: CAS #: 4. Chemical name: CAS #: 4. Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.19 In plastic parts > 25 g, the postconsumer recycled plastic materi				in parts containing	9		
P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Image: Image	D7 45						
P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Imarking: FR(40) P7.17 Att. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): Imarking: FR(40) P7.17 Att. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): Imarking: FR(40) P7.17 Att. 1: Chemical specifications of flame retardants in printed circuit boards (without components): Imarking: FR(40) P7.18 Att. 1 TBBPA (reactive) (See NOTE B3). Imarking: FR(40) P7.18 Att. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Imarking: FR(40) Comment: No legal limits exist, this is a market requirement. 1. Chemical name: CAS #: 3. Chemical name: CAS #: 4. Chemical name: CAS #: 4. Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: Imarket in plastic parts > 25 g, flame retardant substances/preparations above 0.1% are used which have been assigned the following Risk phrases; and Hazard statements: Imarket in plastic parts > 25 g, flame retardant substances/preparations above 0.1% are used which have been assigned the following Risk phrases; and Hazard statements: Imarket in the product (See Note B6): Imarket in the product (See Note B6): Imarket in attra in answer	P7.15			are low haloge	ו נ	M	
Marking: <i>FR(40)</i> Image: Construct the second	P7 16						
TBBPA (additive), □TBBPA (reactive) (See NOTE B3), ○Other: Brominated Epoxy Resins, CAS #: 26265-08-7 Alt 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: CAS #: 3. Chemical name: CAS #: 4. Chemical name: CAS #: 4. Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardants in plastic parts >25g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6):		Marking:	FR(40)				<u> </u>
26265-08-7 Image: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1 Image: Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Image: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: CAS #: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: CAS #: Confidential 2. Chemical name: CAS #: 3. Chemical name: CAS #: 4. Chemical name: CAS #: 4. Chemical name: CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is or or	P7.17						
Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: CAS #: 2. Chemical name: CAS #: 3. Chemical name: CAS #: 4. Chemical name: CAS #: 4. Chemical name: CAS #: 4. Chemical name: CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is or Or				Resins , CAS #	:		
according ISO 1043-4: Image: According ISO 1043-4: P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Image: Concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: Oligomeric phosphorous compound CAS #: Confidential 2. Chemical name: CAS #: 3. Chemical name: CAS #: 4. Chemical name: CAS #: Alt. 2 Image: CAS #: Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: Image: CAS #: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: Image: CAS #: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): Image: Cas: Cas: Cas: Cas: Cas: Cas: Cas: Cas		26265-0	8-7				
P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: Oligomeric phosphorous compound CAS #: Confidential 2. Chemical name: CAS #: 3. Chemical name: CAS #: 4. Chemical name: CAS #: 4. Chemical name: CAS #: 4. Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is or or				ents) > 25 g			
Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: <i>Oligomeric phosphorous compound</i> CAS #: <i>Confidential</i> 2. Chemical name: CAS #: 3. Chemical name: CAS #: 4. Chemical name: CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is or			g ISO 1043-4:				
concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: Oligomeric phosphorous compound CAS #: Confidential 2. Chemical name: CAS #: 3. Chemical name: CAS #: 4. Chemical name: CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is or	P7.18		aterded plastic parts >25g contain the following flame retardant substance	c/proporations i			
Comment: No legal limits exist, this is a market requirement. 1. Chemical name: Oligomeric phosphorous compound CAS #: Confidential 2. Chemical name: CAS #: 3. Chemical name: CAS #: 4. Chemical name: CAS #: 4. Chemical name: CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is or					1		
1. Chemical name: Oligomeric phosphorous compound CAS #: Confidential 2. Chemical name: CAS #: 3. Chemical name: CAS #: 4. Chemical name: CAS #: 4. Chemical name: CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is or							
2. Chemical name: CAS #: 3. Chemical name: CAS #: 4. Chemical name: CAS #: 4. Chemical name: CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is or		1. Chem	ical name: <i>Oligomeric phosphorous compound</i> CAS #: <i>Confidential</i>				
 4. Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is or 							
Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered;							
Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is . or		4. Chem	ical name: , CAS #:				
Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is . or		Δlt 2					
P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): [YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is or			al specifications of flame retardants in plastic parts >25g according ISO 1043-4:				
assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is or							
The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is or	P7.19	In plastic	parts > 25 g, flame retardant substances/preparations above 0,1% are used whic	h have been			
 P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is or 		0	6 1 <i>j</i>				
If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is or				ee note B5)			
 a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is or 	P7.20*					\boxtimes	
a percentage of total plastic by weight) is or				t (aclouisted c-			
or				it (calculated as			
			e weight of recycled material is g.				

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model number *	Model number * 82N5		Lenovo
Issue date *	2021-3-24		LEHOVO
Product environm	nental attributes - Market requirements (continued)		Requirement met

Item

Requirement met Yes No n.a.

	Material and su	bstance requirements	(continued)					
P7.21*		material content is use		NOTE B7):				
	If VES: at least o	ne of the two alternativ	es below shall be ansy	wered:				
	,			,	ated as a percentage of			
		c by weight) is %.						
	or b) The weight	of the biobased plastic	material is a					
P7.22*		e free from mercury, i.e.		n				
		d specify: Number of la		num mercury content p	per lamp: mg			
P8	Batteries							
P8.1*	Battery chemical	composition: LI-ION P	olymer battery					
P9		ption (See NOTE B8)						
P9.1		he following power leve						
Energy mo	de *	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference/Standard for energy modes and test method *			
Peak (On-	max)	95 W	95 W	95 W	Full load			
Categor	<u>y 2</u>							
Short Idle	State - WOL	7.49 W	7.45 W	7.62 W	Use for ENERGY STAR V8.0			
Enabled					registration (P _{idle})			
	State - WOL	3.20 W	3.26 W	3.39 W	Use for ENERGY STAR V8.0			
Enabled					registration (P _{idle})			
Sleep (S3)	- WOL Enabled	0.74 W	0.74 W	0.76 W	Reference			
Sleep (S3)	- WOL Disabled	0.74 W	0.74 W	0.76 W	Use for ENERGY STAR V8.0			
0.000					registration (P _{idle})			
Off (S5) - I	NOL Enabled	0.26 W	0.26 W	0.28 W	Reference			
Off (S5) - I	NOL Disabled	0.26 W	0.26 W	0.28 W	Use for ErP			
EPS No-lo		0.113 W	0.114 W	0.115W				
(External power s wall outlet but dis	supply / charger plugged in th connected from the product.)	e						
PTEC *		W	W	W				
	ergy Consumption							
ETEC *	aray Canaumation	25.33 kWh/year	25.28 kWh/year	25.93 kWh/year	$E_{TEC} = (8760/1000) \times (P_{off} \times 0.25)$			
Annual En	ergy Consumption				+ P _{sleep} x 0.35 + P _{long_ldle} x 0.10+ P _{short Idle} x 0.30)			
		Poff: Off Mode(S5) - W	OL Enabled; Psleep: Slee	ep Mode(S3) - WOL Enab	led; P _{idle} : Idle State - WOL Enabled			
External P	ower Supply Efficie	ency Level (Internationa						
Display res	solution * : 5.18 me	gapixels						
		save mode: 30 minutes			H			
P9.2*	0,	t the energy save funct		e product.				
P9.3		class (monitors only):						
P10	Emissions	(
		- Declared according t	o ISO 9296 (See NOT	E B9)				
P10.1	Mode	Mode description			nit A-weighted sound power level, <i>L_{WA,c}</i> (B)			
	Idle	* Idle (Operating)		* 2.2	· · · · · · · · · · · · · · · · ·			
	Operation			* 4.5				
	Other mode	Declared A-weighted sour	nd pressure level (dB) L_{n^2}	m 16.3 (operator pos	ition desktop – idle)			
	Other mode	Declared A-weighted sour			ition desktop – operating)			
	Measured accord		ECMA-74	I				
		Other	(only if not covered b	y ECMA-74)				

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

Model nu	mber *	82N5			Logo	Long		
Issue dat	te *	2021-3-24				Leno	VO.	-
Product	environ	nental attribut	es - Market requirements	(continued)		Require	ment	met
Item						Yes	No	n.a.
		magnetic emiss						
P10.4	program	ı(s): MPŔ-II(3 piı	the requirement for low frequer AC adapter only)	cy electromagnetic field	s of the following volur	ntary 🔀		
P12		mics for compu						
P12.1*		-	gonomic requirements of ISO 9			\square		
P12.2*	The phy	sical input device	e meets the requirements of ISC) 9995 and ISO 9241-41	0.	\boxtimes		
P13		ing and docume						
P13.1*	Product Product	packaging mater	ial type(s): <i>paper(manual)</i> ial type(s): <i>corner paper</i> weigh	nt (kg): 0.26 weight (kg): 0.05 nt (kg): 0.060 nt (kg): 0.077				
P13.2*	Product	plastic primary p	ackaging is free from PVC.			\boxtimes		
P13.3*	For product primary corrugated fiberboard packaging, specify the contained percentage of minimum post-							
P13.4*		media for user a ic 🔀, Paper 🔀	nd product documentation (tick , Other	box):				
P13.5	Ùser an		is item if paper documentation entation on paper media is chlo					
	Element	chlorine-free al chlorine-free ed chlorine-free						
P14	Volunta	ry programs						
P14.1	The pro	duct meets the re	quirements of the following vol	untary program(s):				
P15	Eco-lab Eco-lab	el:	Criteria version: 8.0 Criteria version: Criteria version: (See NOTE B10)	Date: 2021/3/17 Date: Date:	Product category: 2 Product category: Product category:			
P15 P9			· ·	any description of the	tootod product confi	invertion		
<u> </u>	NOTE: S informat knowled	Supplier makes n ion contained in ge available at th here is approxir	f specific configuration may voor or representations, guarantees, this document. All information put time of completion, and support nate and provided for information to the specific or the second seco	assurances or warrantie rovided by supplier in th lier shall have no obligation	es whether express or i is document is provide tion to update such info	implied, regardin d based on supp prmation. The int	olier's formati	ion
P9	See Ene	ergy Star Qualifie	d Notebooks & Tablet Compute s://www.energystar.gov/produc					

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B2

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1
Regulation (EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7
Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances)	P1.3, P5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) No 1272/2008 (CLP Regulation)	P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1

Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	Yoga Slim 7 Pro 14ACH5 O, Yoga 14sACH 2021 O	Logo
Model number *	82N5	
Issue date *	2021-3-24	Lenovo
Additional information		

P7.1.1	Product environmental attributes				
d)	Year of manufacture:				2021
e)	Etec value (kWh) per ErP Lot 3 Catego disabled and if the system is tested with				cards (dGfx) are
F)	Etec value (kWh) per ErP Lot 3 Categor enable	ry and capability adjust	tments applied when a	all discrete graphics	cards (dGfx) are
		Category A (according to ErP Lot 3)	Category B (according to ErP Lot 3)	Category C (according to ErP Lot 3)	Category D (according to ErP Lot 3)
	Memory over base [GB]	16			
ents sting	Additional internal storage	No (Yes / No)	(Yes / No)	(Yes / No)	(Yes / No)
capability adjustments applied during testing	Discrete television tuner	No (Yes / No)	(Yes / No)	(Yes / No)	(Yes / No)
ability a lied du	Discrete Audio Card	No (Yes / No)	(Yes / No)	(Yes / No)	(Yes / No)
capa app	Discrete graphics Card(s) [number / #]	No #: (Yes / No)	#: (Yes / No)	#: (Yes / No)	#: (Yes / No)
	Category of discrete graphics Card(s)				
Test results	Etec Value (kWh) - dGfx disabled all discrete graphics cards (dGfx) are disabled/ UMA is active for switchable graphics/ product has no graphics cards (dGfx)	11.05			
Test n	Etec Value (kWh) - dGfx enabled all discrete graphics cards (dGfx) are enabled				
g)	Idle state power demand (Watts);		I		A: 3.39
ו)	Sleep mode power demand (Watts);				A: 0.76
)	Sleep mode with WOL enabled power de	emand (Watts) (where	enabled);		A: 0.76
)	Off mode power demand (Watts);				A: 0.28
<)	Off mode with WOL enabled power dem	and (Watts) (where en	abled);		A: 0.28
)	Internal power supply efficiency at 10 %,	, 20 %, 50 % and 100 °	% of rated output pow	er (if applicable):	
	10% 20% 50%	100% Avera	age		
m)	External power supply efficiency (if appli	cable)*:			
	Average active efficiency: 89.27% 89.2	20% 90.57%			
	*internal note: show values for all available external p				
o)	Minimum number of loading cycles that t	the batteries can withs	tand (applies only to r	otebook computers):	300CYCLES
p-1)	Measurement methodology used to dete	ermine information mer NA	ntioned in points (I) – i	nternal PSU efficiency	•
o-2)	Measurement methodology used to dete	ermine information mer		external PSU efficient	cy:

(p-3)	Measurement metho	dology used to determine information mentioned in p EN 50563:2011 measurement methodo		
(p-4)		dology used to determine information mentioned in r Point P9.1 in the Product IT Eco Declaration:	naximum, idle, sleep, off mode	
		EN 62623:2013 measurement methodo	blogy	
(q)	Sequence of steps for	or achieving a stable condition with respect to power	demand::	
		EN 62623:2013 measurement methodo	blogy	
(r)	Description of how s	leep and/or off mode was selected or programmed:		
		EN 62623:2013 measurement methodo	blogy	
(s)	Sequence of events off mode:	required to reach the mode where the equipment au	tomatically changes to sleep and/or	
	refe	er to power management, 30mins automatically re	eaches sleep mode	
(t)		te condition before the computer automatically re- s not exceed the applicable power demand requirement		10
(u)	Length of time after	r a period of user inactivity in which the compute	r automatically reaches a power	NA
(v)		wer power demand requirement than sleep mode (in ore the display sleep mode is set to activate after		30
(w)		nergy-saving potential of power management function		30
		refer to user manual		
(x)	User information on	how to enable the power management functionality:		
		refer to user manual		
(z)	the electricity supply	measurements: — test voltage in V and frequency in system, — information and documentation on the in		
	used for electrical tes	sting: 230V, 50GHz, Total Harmonic Distortion	1 <2 %	
A				
Additio	nal Notebook Batter	Battery[ies] not user replaceable	Battery[ies] user replaceable	n/a
		The battery[ies] in this product cannot be easily replaced by users themselves. ¹⁾		
Internal/	built-in Battery			
External	/detachable Battery			
Bios Bao	ckup Battery			
Other:				
Addition	al information	1	I	
		asily replaced by users themselves. родукт не може да се замени[ят] лесно от самите потребител	пи.	
as baterías d	le este producto no pueden s	er sustituidas fácilmente por los propios usuarios. neměli provádět sami uživatelé.		
rugeren kan	ikke uden videre udskifte bat	teriet/batterierne i dette produkt.		
asutajad ei s	aa selle toote akut/akusid ise		/erden.	
		ούν να αντικατασταθούν εύκολα από τους ίδιους τους χρήστες iit ne peuvent être facilement remplacée(s) par les utilisateurs eu	x-mêmes.	
	ože lako zamijeniti Bateriju sa batterie in guesto prodotto no	am u ovom proizvodu. on può/possono essere facilmente sostituita/e dall'utente.		
etotāji paši n	nevar nomainīt šā ražojuma a aterijos [bateriju] pats vartoto	kumulatoru(-us).		
termék akku	ımulátorát/akkumulátorait a fe	elhasználó nem tudja egyedül egyszerűen kicserélni.		
atteriet [ene]	i dette produktet kan ikke let			
		e gebruiker niet gemakkelijk vervangbaar. wymienić baterii w tym produkcie.		
ou as bateri	as deste produto não podem	ser facilmente substituídas pelos próprios utilizadores.		
	iile) din acest nrodus nu post			
	omto výrobku nemôže vymie	e (pot) fi ușor înlocuită (înlocuite) de utilizatorii înșiși. ňat používatel.		
terij/baterije män tuottee	tomto výrobku nemôže vymie v tem izdelku uporabniki sar	e (pot) fi ușor înlocuită (înlocuite) de utilizatorii înșiși. ňat používateľ. mi ne morejo zlahka zamenjati. osti käyttäjän vaihdettavissa.		

Bu üründeki batarya(lar) kullanıcılar tarafından kolaylıkla değiştirilemez.