



新普科技股份有限公司
新世電子(常熟)有限公司
新普科技(重慶)有限公司
華普電子(常熟)有限公司
Simplo Technology Co., Ltd.
Simplo Technology(Changshu)Inc.
Simplo Technology(Chongqing)Inc.
Huapu Technology(Changshu)Inc.

Issued/Revised date : September 27 2019
Document No. : SDS_Simplo-1904

Explanatory sheet about safety of product for transportation (Safety Data Sheet for transportation)

1. Basic item

Product name	Lithium-Ion Rechargeable Battery Pack
UN number:	3480
Product code:	Refer to Table 1.
model name:	Refer to Table 1.
Manufacturer Name:	Simplo Technology Co., Ltd.
Address:	No.471, Sec.2, Pa Teh Rd., Hu Kou 303, Hsin Chu Hsien, Taiwan
Phone number:	+886-3-5695920
Fax number:	+886-3-5695931

2. Product information

Basic composition of the product This product is a battery which consists of such main component as core battery pack assembled with some Lithium ion cells. And it consists of any combination of plastic casing, tube casing, protection circuit boards, safety devices and interface terminals

3. Safety Information

Simplo certifies the battery has passed and satisfied the UN Manual of Tests and Criteria Part III, sub-section 38.3 testing in Simplo shipping. - Simplo manufactured the battery under the quality management program required in UN Model regulations 2.9.4(e)..

3-1: Battery pack

1. The Watt-hour rating of the battery is not more than 100Wh.
The Watt-hour rating of the component Lithium ion cells is not more than 20Wh.
Refer to Appendix “SDS_Simplo-1904”.
2. Packages of the battery satisfy the following conditions when Simplo ships.
 - (1) The package has passed the drop test from the height of 1.2m.
 - (2) The package net weight is not more than 10kg.
 - (3) The package is marked and labeled according to requirement of Packing Instruction 965 Section IB stated in ICAO’s and IATA’s dangerous goods regulations.
3. The battery is not defective for safety reasons, not damaged. It is not collected battery for recycling or disposal.
4. The battery is not subject to the fully regulated requirements for Dangerous Goods in ocean and ground transportation.
5. The battery should be transported by Cargo aircraft as UN3480, Class 9 Dangerous Goods, and state of charge not exceeding 30%, according to Packing Instruction 965 Section IB stated in ICAO’s and IATA’s dangerous goods regulations.



新普科技股份有限公司
 新世電子(常熟)有限公司
 新普科技(重慶)有限公司
 華普電子(常熟)有限公司
 Simplo Technology Co., Ltd.
 Simplo Technology(Changshu)Inc.
 Simplo Technology(Chongqing)Inc.
 Huapu Technology(Changshu)Inc.

Table. 1 Model list of application

Battery Part Numbers			Battery Information						
Lenovo ASM Lenovo PN Part Number	Lenovo FRU Part Number	Lenovo Model Name	MSDS Type #	UN DOT 38.3 Test Certificate	Cell Voltage (V)	Battery Voltage (V)	Watt hour Rating (Wh)	Weight (grams)	Equivalent Lithium Content (grams)
31507326		L14M6AA0	SDS_Simplo-1904	31507326_UN38.3	3.6	10.8	48	280	3.96
121000928		N/A	SDS_Simplo-1904	121000928_UN38.3	3.7	11.1	24	170	1.98
121000935		L09M6Y02	SDS_Simplo-1904	121000935_UN38.3	3.7	11.1	49	300	3.96
121001095		L10M6F21	SDS_Simplo-1904	121001095_UN38.3	3.7	11.2	63	330	5.04
121001123		N/A	SDS_Simplo-1904	121001123_UN38.3	3.7	11.1	49	290	3.96
121500043		L11M6Y01	SDS_Simplo-1904	121500043_UN38.3	3.6	10.8	48	290	3.96
121500100		L10M3Z11	SDS_Simplo-1904	121500100_UN38.3	3.7	11.1	24	165	1.98
121500230		L13M3F01	SDS_Simplo-1904	121500230_UN38.3	3.75	11.25	36	185	2.88
121500270		L12M4A02	SDS_Simplo-1904	121500270_UN38.3	3.6	14.4	32	205	2.64
121000951		N/A	SDS_Simplo-1904	121000951_UN38.3	3.7	11.1	49	300	3.96
121000959		L09M8Y21	SDS_Simplo-1904	121000959_UN38.3	3.6	14.4	63	390	5.28
121001047		L09M3Z11	SDS_Simplo-1904	121001047_UN38.3	3.7	11.1	24	160	1.98
121001124		L10M3Z11	SDS_Simplo-1904	121001124_UN38.3	3.7	11.1	24	168	1.98
121001130		L09M8Y21	SDS_Simplo-1904	121001130_UN38.3	3.6	14.4	63	390	5.28
121500085		N/A	SDS_Simplo-1904	121500085_UN38.3	3.7	11.1	49	300	3.96
121500099		N/A	SDS_Simplo-1904	121500099_UN38.3	3.7	11.1	49	155	3.96
121500101		L10M6Y12	SDS_Simplo-1904	121500101_UN38.3	3.7	11.1	49	291	3.96
121500202		L12M4F02	SDS_Simplo-1904	121500202_UN38.3	3.75	15	48	220	3.84
121500203		L12M4F01	SDS_Simplo-1904	121500203_UN38.3	3.75	15	48	240	3.84
5B10H13099		L14M4A01	SDS_Simplo-1904	5B10H13099_UN38.3	3.6	14.4	32	185	2.64
5B10K10169		L14M4A01	SDS_Simplo-1904	5B10K10169_UN38.3	3.6	14.4	32	185	2.64
5B10K10191		L12M4A02	SDS_Simplo-1904	5B10K10191_UN38.3	3.6	14.4	32	205	2.64
5B10K10217		L14M4E01	SDS_Simplo-1904	5B10K10217_UN38.3	3.75	15	42	200	3.36
5B10K80878		L15M4E01	SDS_Simplo-1904	5B10K80878_UN38.3	3.72	14.88	42	230	3.37
SB10K10385		L14M6AA0	SDS_Simplo-1904	SB10K10385_UN38.3	3.6	10.8	48	280	3.96
121500212		L12M6Z53	SDS_Simplo-1904	121500212_UN38.3	3.6	10.8	48	290	3.96
5B10G10726		L14M6F01	SDS_Simplo-1904	5B10G10726_UN38.3	3.75	11.25	72	340	5.76
5B10H13094		L14M4E01	SDS_Simplo-1904	5B10H13094_UN38.3	3.75	15	42	204	3.36
SB10F46468	00HW030		SDS_Simplo-1904	SB10F46468_UN38.3 SDI	3.75	15	96	475	7.68
45N1762	45N1763		SDS_Simplo-1904	45N1762_UN38.3	3.6	10.8	48	296	3.96
45N1162	45N1163		SDS_Simplo-1904	45N1162_UN38.3	3.6	10.8	48	290	3.96
45N1132	45N1133 45N1736	L12M6Z53	SDS_Simplo-1904	45N1132_UN38.3	3.6	10.8	48	293	3.96



新普科技股份有限公司
 新世電子(常熟)有限公司
 新普科技(重慶)有限公司
 華普電子(常熟)有限公司
 Simple Technology Co., Ltd.
 Simple Technology(Changshu)Inc.
 Simple Technology(Chongqing)Inc.
 Huapu Technology(Changshu)Inc.

MATERIAL SAFETY DATA SHEET

Issued/Revised date : September 27 2019
 Document No. : SDS_Simplo-1904

1. Product and Company Identification

Product Identification :

Product name: Lithium ion rechargeable battery cell
 Product code: All Cylindrical models SDI manufactured
 Cell manufacturers: SAMSUNG SDI Co.,LTD

2. Hazards Identification

Class Name : Not applicable for regulated class

Hazard : It may cause heat generation or electrolyte leakage if battery terminals contact with other metals.
 Electrolyte is flammable. In case of electrolyte leakage, move the battery from fire immediately.

Toxicity : Vapor generated from burning batteries, may make eyes, skin and throat irritate.

3. Composition / Identification on Ingredients

IMPORTANT NOTE:

The battery should not be opened or burned since the following ingredients contained within the battery that could be harmful under some circumstance if exposed or misused.

The cell contains neither metallic lithium nor lithium alloy.

Composition :

CAS Number: Not specified (3-1 and 3-2)

- 3-1. Cases: Plastic Material Not dangerous
- 3-2. Printed Circuit Board Assembly: Not dangerous
- 3-3. Lithium Ion Cell :

Hazardous Ingredients	%	CAS Number
Cobalt oxide	< 30 %	1307-96-6
Manganese dioxide	< 30 %	1313-13-9
Nickel oxide	< 30 %	1313-99-1
Carbon	< 30 %	7440-44-0
Electrolyte (*)	< 20 %	616-38-6
Polyvinylidene fluoride (PVdF)	< 10 %	24937-79-9
Aluminium foil	2 - 10 %	7429-90-5
Copper foil	2 - 10 %	7440-50-8
Aluminium and inert materials	5 - 10 %	7429-90-5

4. First Aid Measures

The product contains organic electrolyte. In case of electrolyte leakage from the battery, actions described below are required.



新普科技股份有限公司
 新世電子(常熟)有限公司
 新普科技(重慶)有限公司
 華普電子(常熟)有限公司
 Simple Technology Co., Ltd.
 Simple Technology(Changshu)Inc.
 Simple Technology(Chongqing)Inc.
 Huapu Technology(Changshu)Inc.

Eye contact : Flush the eyes with plenty of clean water for at least 15 minutes immediately, without rubbing, and call a doctor. If appropriate procedures are not taken, this may cause an eye irritation.

Skin contact : Wash the contact areas off immediately with plenty of water and soap. If appropriate procedures are not taken, this may cause sores on the skin.

Inhalation : Remove to fresh air immediately, and call a doctor.

5. Fire Fighting Measures

Use specified extinguishers (gas, foam, powder) and extinguishing system under the Fire Defense Law. Since corrosive gas may be produced at the time of fire extinguishing, use an air inhalator when danger is predicted.

Use a large amount of water as a supportive measure in order to get cooling effect if needed. (Indoor/outdoor fire hydrant)

Carry away flammable materials immediately in case of fire.

Move batteries to a safer place immediately in case of fire.

6. Accidental Release Measures

Wipe off with dry cloth

Keep away from fire

Wear safety goggles, safety gloves as needed

7. Precautions for Safe Handling and Use

Storage : Store within the recommended limit of -20°C to 45°C (-4°F to 113°F), well-ventilated area.

Do not expose to high temperature (60°C/140°F). Since short circuit can cause burn hazard or gas release, do not store with metal jewelry, metal covered tables, or metal belt. The lithium ion battery should be between 25% and 75% of full charge when stored for a long period of time. Store in a cool, dry, well-ventilated area. And temperature above 100 Celsius degree can result in loss of battery performance, leakage, or rust. Do not expose the battery to open flames..

Handling : Do not disassemble, remodel, or solder. Do not short + and - terminals with a metal. Do not open the battery.

Charging : Charge within the limits of 0°C to 45°C (32°F to 113°F) temperature. Charge with specified charger designed for this battery.

Discharging : Discharge within the limits of -20°C to 60°C (-4 °F to 140°F) temperature. Disposal :

Dispose in accordance with applicable federal, state and local regulations. Caution : Fire, Explosion, and Severe Burn Hazard. Do not Crush, Disassemble, Heat Above 100°C/212°F, or Incinerate.

8. Exposure Controls / Personal Protection (In case electrolyte is leaked from battery)

Acceptable concentration : Not specified in ACGIH. Facilities : Provide appropriate ventilation such as local ventilation system in the storage. Protective clothing : Gas mask for organic gases, safety goggle, safety glove.

9. Physical and Chemical Properties

State	Solid
Odor	N/A
PH	N/A
Vapor pressure	N/A



新普科技股份有限公司
新世電子(常熟)有限公司
新普科技(重慶)有限公司
華普電子(常熟)有限公司
Simple Technology Co., Ltd.
Simple Technology(Changshu)Inc.
Simple Technology(Chongqing)Inc.
Huapu Technology(Changshu)Inc.

Vapor density	N/A
Boiling point	N/A
Solubility in water	Insoluble
Specific gravity	N/A
Density	N/A

10. Stability and Reactivity

External short-circuit, deformation by crush, high temperature (over 100°C) exposure of a battery cause generation of heat and ignition.

11. Toxicological Information

Acute toxicity : No information as a battery.
Local effects : No information as a battery.

12. Ecological Information

When exhausted battery is buried in the ground, corrosion may be caused on the outer case of battery and electrolyte may be oozed. There is no information on environmental influence.

13. Disposal Consideration

When battery is disposed, isolate positive (+) and negative (-) terminals of the battery to avoid those terminals from touching each other. Batteries may be short-circuited when piled up or mixed with the other batteries in disorder. Dispose in accordance with applicable federal, state and local regulations

14. Transport Information

In the case of transportation, avoid exposure to high temperature and prevent the formation of any condensation. Take in a cargo of them without falling, dropping and breakage. Prevent collapse of cargo piles and wet by rain. The container must be handled carefully. Do not give shocks that result in a mark of hitting on a cell. Please refer to Section 7-HANDLING AND STORAGE also.

UN regulation

UN number: 3480 (3481 when the battery is contained in equipment or packed with equipment) Proper shipping name: Lithium ion batteries (“lithium ion batteries contained in equipment” or “lithium ion batteries packed with equipment”) Class: 9 * * Although this product meets the criteria of “dangerous goods” and are classified as “lithium ion batteries”, depending on the battery’s total capacity in the packaging, etc., they may not be subject to the fully regulated provisions.

Regulation depends on region and transportation mode

Worldwide - Air transportation:

ICAO/IATA-DGR [packing instruction 965 section IB or II] (When shipping batteries “packed with” or “contained in” equipment, use packing instruction 966 or 967 as appropriate.)

Worldwide - Ocean transportation:

IMO-IMDG Code [special provision 188 and 230]

Europe - Ground transportation: ADR [special provision 188 and 230]

** Instructions or provisions in the box brackets are conditions to make the battery cell exempted from full regulation.*



新普科技股份有限公司
新世電子(常熟)有限公司
新普科技(重慶)有限公司
華普電子(常熟)有限公司
Simple Technology Co., Ltd.
Simple Technology(Changshu)Inc.
Simple Technology(Chongqing)Inc.
Huapu Technology(Changshu)Inc.

15.Regulatory Information

IMDG Code: International Maritime Dangerous Goods (IMDG) Code [2018 Edition](#)

ICAO TI: International Civil Aviation Organization (ICAO) Technical Instructions for the Safe Transport of Dangerous Goods by Air [2019-2020 Edition](#)

IATA DGR: International Air Transport Association (IATA) Dangerous Goods Regulations ([60th Edition, 2019](#))

16.Other Information

The information contained herein is furnished without warranty of any kind, Users should consider this data only as a supplement to other information gathered by them and must make independent determinations of the suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers.