

## Explanatory sheet about safety of product for transportation (Safety Data Sheet for transportation)

### 1. Basic item

Product name: Lithium ion rechargeable battery (including lithium polymer battery)  
Product identification: Refer to Table 1.  
Manufacturer: SANYO Electric Co., Ltd., Panasonic group  
Address: 222-1, Kaminaizen, Sumoto, Hyogo, Japan  
Phone number: +81-799-23-3931  
E-mail: prb-bp-ta@ml.jp.panasonic.com

### 2. Product information

- The UN number of this product is 3480.
- This product is "battery" that combines some of the cells, and may be accompanied by outer case or tube covering, protective device, input / output terminal, and the like.
- The watt-hour rating of this product does not exceed 100 Wh.
- SANYO guarantee that this product has passed the test of the UN Manual of Tests and Criteria Part III, sub-section 38.3.
- SANYO manufacture this product under the quality management program required by UN Model Regulations 2.9.4 (e).
- At the time of shipment from SANYO, the package of this product satisfies the following conditions.
  - Passed the 1.2 m drop test.
  - The net quantity of one package does not exceed 10 kg.
  - Marked and labeled according to requirement of the Packing Instruction 965 Section IB stated in ICAO's and IATA's dangerous goods regulations.
  - Products identified as damaged or defective for safety reasons are not included. Also, products recovered for disposal or recycling are not included.

### 3. Transportation guidelines

- Guidelines for using packages shipped from SANYO are as follows.
  - In air transportation, it is necessary to ship by cargo aircraft at a state of charge not exceeding 30% of their rated design capacity with Class 9 Dangerous Goods Label according to requirement of the Packing Instruction 965 Section IB (or more stringent Packing Instruction) stated in ICAO's and IATA's dangerous goods regulations.
  - In ocean and ground transportation, it is necessary to ship according to UN Model Regulations. But the package is not subject to the fully regulated requirements for Dangerous Goods.

### 4. Appendix

Cell's safety data sheet for product  
Refer to Appendix "SDS (SDS-IBH-00485)".



---

H. Kuroda Senior Manager  
Battery Pack Engineering Department  
Energy Solutions Business Division  
SANYO Electric Co., Ltd.  
Panasonic Group

Table.1 Model list of application

SDS-BAH-06113

Battery Part Numbers			Battery Information						
Lenovo ASM Lenovo PN Part Number	Lenovo FRU Part Number	Lenovo model name	MSDS Type #	UN DOT 38.3 Test Certificate	Cell Voltage (V)	Battery Voltage (V)	Watt hour Rating (Wh)	Weight (grams)	Equivalent Lithium Content (grams)
31504999		31504999	SDS-IBH-00485	31504999_UN38.3	3.6	10.8	45	240	3.70
42T4523	42T4643 42T4522		SDS-IBH-00485	42T4523_UN38.3	3.6	10.8	44	307	3.60
42T4535	42T4646 42T4534		SDS-IBH-00485	42T4535_UN38.3	3.6	14.4	29	205	2.40
42T4563	42T4657 42T4562		SDS-IBH-00485	42T4563_UN38.3	3.6	14.4	29	256	2.40
42T4565	42T4564		SDS-IBH-00485	42T4565_UN38.3	3.6	14.4	67	465	5.52
42T4689	42T4832 42T4688		SDS-IBH-00485	42T4689_UN38.3	3.7	11.1	44	312	3.60
42T4820	42T4821		SDS-IBH-00485	42T4820_UN38.3	3.7	11.1	40	312	3.60
42T5209	42T4661		SDS-IBH-00485	42T5209_UN38.3	3.6	14.4	66	455	5.46
45N1018	45N1019		SDS-IBH-00485	45N1018_UN38.3	3.7	14.8	29	198	2.40
45N1020	45N1709		SDS-IBH-00485	45N1020_UN38.3	3.7	14.8	29	198	2.34
45N1036	45N1037		SDS-IBH-00485	45N1036_UN38.3	3.6	10.8	44	297	3.60
45N1038	45N1143		SDS-IBH-00485	45N1038_UN38.3	3.7	11.1	44	297	3.51
45N1108	45N1109 45N1773		SDS-IBH-00485	45N1108_UN38.3	3.7	11.1	24	135	1.93
45N1116	45N1117 45N1765		SDS-IBH-00485	45N1116_UN38.3	3.7	11.1	24	140	1.93
45N1124	45N1125 45N1775		SDS-IBH-00485	45N1124_UN38.3	3.7	11.1	24	154	1.93
45N1744	45N1745		SDS-IBH-00485	45N1744_UN38.3	3.6	10.8	25	150	2.02
45N1752	45N1753		SDS-IBH-00485	45N1752_UN38.3	3.7	11.1	47	260	3.85
92P1164	42T4629		SDS-IBH-00485	92P1164_UN38.3	3.6	14.4	29	196	2.40
121000904		L09S8L09	SDS-IBH-00485	121000904_UN38.3	3.7	7.4	68	450	5.52
121500143		L12S3P52	SDS-IBH-00485	121500143_UN38.3	3.7	11.1	24	135	1.88
121500213		L12S3P53	SDS-IBH-00485	121500213_UN38.3	3.7	11.1	24	154	1.93
5B10K88299		L15S2TB0	SDS-IBH-00485	5B10K88299_UN38.3	3.65	7.3	27	165	2.20
5B10M41935		L16S3P24	SDS-IBH-00485	5B10M41935_UN38.3	3.65	10.95	45	240	3.70
SB10F46462	00HW024		SDS-IBH-00485	SB10F46462_UN38.3	3.7	11.1	24	137	1.93
SB10J78988	00HW040		SDS-IBH-00485	SB10J78988_UN38.3	3.7	11.1	47	270	3.85
SB10J79002	01AV405		SDS-IBH-00485	SB10J79002_UN38.3	3.8	11.4	26	135	2.08
SB10K97568	01AV411		SDS-IBH-00485	SB10K97568_UN38.3	3.65	10.95	45	240	3.70
SB10K97571	01AV414		SDS-IBH-00485	SB10K97571_UN38.3	3.85	15.4	32	186	2.52
SB10K97576	01AV419		SDS-IBH-00485	SB10K97576_UN38.3	3.85	11.55	24	116.5	1.87
SB10K97579	01AV422		SDS-IBH-00485	SB10K97579_UN38.3	3.85	11.55	24	140	1.87

Battery Part Numbers			Battery Information						
Lenovo ASM Lenovo PN Part Number	Lenovo FRU Part Number	Lenovo model name	MSDS Type #	UN DOT 38.3 Test Certificate	Cell Voltage (V)	Battery Voltage (V)	Watt hour Rating (Wh)	Weight (grams)	Equivalent Lithium Content (grams)
SB10L84123	00UR892		SDS-IBH-00485	SB10L84123_UN38.3	3.85	15.4	32	152	2.50
SB10F46469	00HW031			SB10F46469_UN38.3	3.7	11.1	24	135	1.93
SB10F46473	00HW035			SB10F46473_UN38.3	3.8	11.4	26	151	2.08
SB10J79004	01AV407			SB10J79004_UN38.3	3.8	11.4	26	135	2.08
SB10F46476	00HW038			SB10F46476_UN38.3	3.7	11.1	24	137	1.94

*\* This document has been prepared taking into account regulations as of January 1, 2020*

## Safety data sheet for product

### 1. PRODUCT AND COMPANY IDENTIFICATION

- Product name: Lithium ion rechargeable battery cell
- Product code: None  
(All prismatic models Sanyo manufactured and whose capacity is less than or equal to 5.4Ah, including the cell branded as Panasonic, excluding the cell whose two or more short / middle / long side excess 12mm/85mm/110mm.)
- Company name: Sanyo Electric Co., Ltd., Panasonic group
- Address: 222-1 , Kaminaizen, Sumoto City, Hyogo, Japan
- Telephone number: +81-799-24-4111
- Fax number: +81-799-23-2879
- Emergency telephone number: [Daytime of business day] +81-799-23-3931  
[Night and holiday] +81-799-24-4131

### 2. HAZARDS IDENTIFICATION

For the battery cell, chemical materials are stored in a hermetically sealed metal or metal laminated plastic case, designed to withstand temperatures and pressures encountered during normal use. As a result, during normal use, there are no physical hazards such as ignition, explosion and chemical hazards due to leakage of battery contents.

However, if exposed to a fire, added mechanical shocks, decomposed, added electric stress by miss-use, the gas release vent will be operated. The battery cell case will be breached at the extreme, hazardous materials may be released.

Also, if it is heated strongly by surrounding fires or the like, there is a possibility that irritating or harmful gas may be generated.

- GHS classification: Not available  
(This product is outside the scope of GHS system since it's considered as an "article".)
- Most important hazard and effects  
Human health effects:  
Inhalation: The steam of the electrolyte has an anesthesia action and stimulates a respiratory tract.  
Skin contact: The steam of the electrolyte stimulates a skin. The electrolyte skin contact causes a sore and stimulation on the skin.  
Eye contact: The steam of the electrolyte stimulates eyes. The electrolyte eye contact causes a sore and stimulation on the eye. Especially, substance that causes a strong inflammation of the eyes is contained.  
Environmental effects: Since a battery cell remains in the environment, do not throw out it into the environment.
- Specific hazards:  
If the electrolyte contacts with water, it will generate detrimental hydrogen fluoride.  
Since the leaked electrolyte is inflammable liquid, do not bring close to fire.

\* This document has been prepared taking into account regulations as of January 1, 2020

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

- Substance or preparation: Preparation
- Information about the chemical nature of product: \*1

Portion	Material name	CAS No.	Concentration range (wt %)
Positive electrode	Lithium transition metal oxidate (Li[M] <sub>m</sub> [O] <sub>n</sub> *2)	12190-79-3 12031-65-1 12057-17-9 182442-95-1 207803-51-8	20~60
Positive electrode's base	Aluminum	7429-90-5	1~10
Negative electrode	Carbon	7782-42-5 7440-44-0	10~30
Negative electrode's base	Copper	7440-50-8	1~15
Electrolyte	Ethyl methyl carbonate Diethyl carbonate Ethylene carbonate Lithium hexafluorophosphate	623-53-0 105-58-8 96-49-1 21324-40-3	5~25
Outer case	Aluminum	7429-90-5	1~30

\*1 Not every product includes all of these materials.

\*2 The letter M means transition metal and candidates of M are Co, Mn, Ni and Al. One compound includes one or more of these metals and one product includes one or more of the compounds. The letter m and n means the number of atoms.

**4. FIRST-AID MEASURES****Spilled internal cell materials**

- Inhalation:  
Make the victim blow his/her nose, gargle. Seek medical attention if necessary.
- Skin contact:  
Remove contaminated clothes and shoes immediately. Wash extraneous matter or contact region with soap and plenty of water immediately.
- Eye contact:  
Do not rub one's eyes. Immediately flush eyes with water continuously for at least 15 minutes. Seek medical attention immediately.

**A battery cell and spilled internal cell materials**

- Ingestion:  
Wash out mouth thoroughly. Do not make the victim vomit, unless instructed by medical personnel. Seek medical attention immediately.

**5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media: Plenty of water, carbon dioxide gas, nitrogen gas, chemical powder fire extinguishing medium and fire foam.
- Specific hazards: Corrosive gas may be emitted during fire.
- Specific methods of fire-fighting: When the battery burns with other combustibles simultaneously, take fire-extinguishing method which correspond to the combustibles. Extinguish a fire from the windward as much as possible.
- Special protective equipment for firefighters: Refer to Section 8-EXPOSURE CONTROLS / PERSONAL PROTECTION (WHEN THE ELECTROLYTE LEAKS)

*\* This document has been prepared taking into account regulations as of January 1, 2020*

## 6. ACCIDENTAL RELEASE MEASURES

Spilled internal cell materials, such as electrolyte leaked from a battery cell, are carefully dealt with according to the followings.

- Precautions for human body:  
Remove spilled materials with protective equipment (refer to Section 8-EXPOSURE CONTROLS / PERSONAL PROTECTION (WHEN THE ELECTROLYTE LEAKS)). Do not inhale the gas as much as possible. Moreover, avoid touching with as much as possible.
- Environmental precautions: Do not throw out into the environment.
- Method of cleaning up: The spilled solids are put into a container. The leaked place is wiped off with dry cloth.
- Prevention of secondary hazards: Avoid re-scattering. Do not bring the collected materials close to fire.

## 7. HANDLING AND STORAGE

- Handling suggestions
  - Do not connect the positive terminal to the negative terminal with electrical wire or chain.
  - Avoid polarity reverse connection when installing the battery to an instrument.
  - Do not wet the battery with water, seawater, drink or acid; or expose to strong oxidizer.
  - Do not damage or remove the external tube.
  - Keep the battery away from heat and fire.
  - Do not disassemble or reconstruct the battery; or solder the battery directly.
  - Do not give a mechanical shock or deform.
  - Do not use unauthorized charger or other charging method. Terminate charging when the charging process doesn't end within specified time.
- Storage
  - Do not store the battery with metalware, water, seawater, strong acid or strong oxidizer.
  - Make the charge amount less than or equal to 50% then store at -20~40 degree C in a dry (humidity: 45~85%) place.  
Since deterioration will be faster in the high temperature range than in the low temperature range, so do not keep it in the high temperature range beyond the period that is specified by the seller or owner.
  - Use insulative and adequately strong packaging material to prevent short circuit between positive and negative terminal when the packaging breaks during normal handling. Do not use conductive or easy to break packaging material.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION (WHEN THE ELECTROLYTE LEAKS)

- Control parameters  
ACGIH has not been mentioned control parameter of electrolyte.
- Personal protective equipment
  - Respiratory protection: Respirator with air cylinder, dust mask
  - Hand protection: Protective gloves
  - Eye protection: Goggles or protective glasses designed to protect against liquid splashes
  - Skin and body protection: Working clothes with long sleeve and long trousers

## 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance
  - Physical state: Solid
  - Form: Prismatic
  - Color: Metallic color (without tube if it has tube)
  - Odor: No odor

*\* This document has been prepared taking into account regulations as of January 1, 2020*

#### 10. STABILITY AND REACTIVITY

- Stability: Normally stable unless a strong shock is applied or heated strongly
- Possibility of hazardous reactions: Damage to the container may cause leakage of contents. Contents may leak or ignite due to temperature rise.
- Conditions to avoid: Crushing or deformation, use and storage at 80 degree C or higher or at high humidity. Usage at a voltage or a current outside the rating and external short circuit.
- Incompatible materials: Conductive material such as water or metal pieces. Oxidizing agent such as bleach.
- Hazardous decomposition products: Irritating or harmful gases are released if a leakage or fire occurs.

#### 11. TOXICOLOGICAL INFORMATION

##### **Organic Electrolyte**

- Acute toxicity:  
LD<sub>50</sub>, oral - Rat 2,000mg/kg or more
- Irritating nature: Irritative to skin and eye

#### 12. ECOLOGICAL INFORMATION

- Persistence/degradability:  
Since a battery cell and the internal materials remain in the environment, do not bury or throw out into the environment.

#### 13. DISPOSAL CONSIDERATIONS

- Recommended methods for safe and environmentally preferred disposal:

##### **Product (waste from residues)**

Specified collection or disposal of lithium ion battery is required by the law like as "battery control law" in several nations. Collection or recycle of the battery is mainly imposed on battery's manufacturer or importer in the nations recycle is required.

##### **Contaminated packaging**

Neither a container nor packing is contaminated during normal use. When internal materials leaked from a battery cell contaminates, dispose as industrial wastes subject to special control.

*\* This document has been prepared taking into account regulations as of January 1, 2020*

#### 14. TRANSPORT INFORMATION

In the case of transportation, avoid exposure to high temperature and prevent the formation of any condensation. Take in a cargo of them without falling, dropping and breakage. Prevent collapse of cargo piles and wet by rain. The container must be handled carefully. Do not give shocks that result in a mark of hitting on a cell. Please refer to Section 7-HANDLING AND STORAGE also.

##### **UN regulation**

- UN number: 3480 (3481 when the battery is contained in equipment or packed with equipment, 3171 when the battery is contained in vehicle and that is only powered by the battery)
- Proper shipping name:  
Lithium ion batteries ("lithium ion batteries contained in equipment" or "lithium ion batteries packed with equipment" for 3481, "Battery-powered vehicle" for 3171)
- Class: 9 \*

*\* Although this product meets the criteria of "dangerous goods" and are classified as "lithium ion batteries", depending on the battery's total capacity in the packaging, etc., they may not be subject to the fully regulated provisions.*

##### **Regulation depends on region and transportation mode**

*\* Instructions or provisions in the box brackets are conditions to make the battery cell exempted from full regulation.*

*Refer the other document issued by the shipper, when you want to know whether such rules are applicable to current battery or what kind of instruction the current package is compliant to.*

- Worldwide - Air transportation:  
ICAO TI/IATA-DGR [packing instruction 965 section IB or II]  
(When shipping batteries "packed with" or "contained in" equipment, use packing instruction 966 or 967 as appropriate. When the battery is contained in vehicle and that is only powered by the battery, use packing instruction 952.)
- Worldwide - Ocean transportation:  
IMO-IMDG Code [special provision 188]
- Europe - Ground transportation:  
ADR [special provision 188]

#### 15. REGULATORY INFORMATION

- Regulations specifically applicable to the product:  
Wastes Disposal and Public Cleaning Law [Japan]  
Law for Promotion of Effective Utilization of resources [Japan]  
US Department of Transportation 49 Code of Federal Regulations [USA]

*\* About overlapping regulations, please refer to Section 14-TRANSPORT INFORMATION.*



*\* This document has been prepared taking into account regulations as of January 1, 2020*

#### 16. OTHER INFORMATION

- This safety data sheet is offered an agency who handles this product to handle it safely.
- The agency should utilize this safety data sheet effectively (put it up, educate person in charge) and take proper measures.
- ***The information contained in this Safety data sheet is based on the present state of knowledge and current legislation.***
- This safety data sheet provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

#### Reference

Dangerous Goods Regulations – 61st Edition Effective 1 January 2020: International Air Transport Association (IATA)  
IMDG Code – 2018 Edition: International Maritime Organization (IMO)  
The European Agreement concerning the International Carriage of Dangerous Goods by Road – 2019:  
The United Nations Economic Commission for Europe (UNECE)

First edition: Apr. 28, 2010  
Prepared and approved by: Battery Pack Engineering Department  
Energy Solutions Business Division  
Sanyo Electric Co., Ltd.  
Panasonic group